

PRODUCTS RESEARCH & CHEMICAL CORPORATION -- PR-383 POLYSULFIDE SEALING, PART A --
8030-00-656-1042

===== Product Identification =====

Product ID:PR-383 POLYSULFIDE SEALING, PART A
MSDS Date:10/01/1985
FSC:8030
NIIN:00-656-1042
Kit Part:Y
MSDS Number: BHQLD
=== Responsible Party ===
Company Name:PRODUCTS RESEARCH & CHEMICAL CORPORATION
Address:5430 SAN FERNANDO ROAD
Box:1800
City:GLENDALE
State:CA
ZIP:91209
Country:US
Info Phone Num:1-818-240-2060
Emergency Phone Num:1-818-240-2060
Preparer's Name:MBY
CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY
Address:5430 SAN FERNANDO RD
Box:1800
City:GLENDALE
State:CA
ZIP:91209
Country:US
Phone:818-240-2060
CAGE:83574
Company Name:PRODUCTS RESEARCH & CHEMICAL
Address:NOW DBA COURTAULDS AEROSPACE
Box:1800
City:GLENDALE
State:CA
ZIP:91209
Phone:818-240-2060
CAGE:DO563

===== Composition/Information on Ingredients =====

Ingred Nam

e:LEAD DIOXIDE
CAS:1309-60-0
RTECS #:OG0700000
OSHA PEL:0.2 MG/M3
ACGIH TLV:0.05 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Health Hazards Acute and Chronic:MOST SIGNIFICANT HEALTH HAZARD IS BY
INHALATION OF AIRBORNE DUST. LEAD DIOXIDE IS THOROUGHLY &
PERMANENTLY WETTED, THERFORE DOESN'T PRESENT A RISK OF
EXPOSURE.INORGANIC LEAD CMPD IN GENERAL ARE TOXIC BY INGESTION.
NOT READILY ABSORBED.AN
EMIA, CENTRAL NER SYS EFFECTS, ABDOMINAL
COLIC, KIDNEY FUNCTION LOSS CAN OCCUR
Effects of Overexposure:ANEMIA, CENTRAL NERVOUS SYSTEM EFFECTS,
ABDOMINAL COLIC OR KIDNEY FUNCTION LOSS CAN OCCUR AT BLOOD LEAD
LEVELS OF 60 MICROGRAMS/100 GRAMS. THE RECOMMENDED MAXIMUM IS
40 MICROGRAMS/100 GRAMS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER. IF IRRITATION PERSISTS,
CONSULT A PHYSICIAN.SKIN: WASH THOROUGHLY
WITH SOAP AND WATER.
INHALATION: NOT APPLICABLE. AND INGESTION: CONSULT A
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER.
Unusual Fire/Explosion Hazard:OXIDIZER.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP SPILLED MATERIAL. CLEAN UP RESIDUE
WITH RAGS AND NON-FLAMMABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. AVOID INGESTION.

===== Exposure Controls/Personal Protection =====

Ventilation:NA

Protective Gloves:OIL RESISTANT GLOVES ARE RECOMMENDED.

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NA

Vapor Pres:NA

Vapor Densi

ty:NA

Spec Gravity:2.6

Evaporation Rate & Reference:NA

Solubility in Water:NEGLIGIBLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NK

Hazardous Decomposition Products:SMOKE; SOOT; CARBON MONOXIDE; CARBON DIOXIDE; LEAD COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.