

CON-LUX COATINGS INC -- ENAMEL 16376 LIGHT GRAY ALKYD GLOSS -- 8010-00-298-2298

=====
Product Identification
=====

Product ID:ENAMEL 16376 LIGHT GRAY ALKYD GLOSS

MSDS Date:01/11/1988

FSC:8010

NIIN:00-298-2298

MSDS Number: BHQST

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908-287-4000 / FAX

908-287-9288

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

VAPOR PRESSURE 2 MM HG @ 20C

CAS:64742-47-8

Fraction by Wt: >1%

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fracti

on by Wt: >1%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:IRRITATION TO SKIN & EYES.IRRITATION TO
RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA & DIZZINESS.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.RESTORE RESPIRATION IF
NECESSARY.EYE:FLUSH IMMEDIATELY W/COPIOU
S ATYS OF WTR FOR 15
MINS.CONSULT A PHYSICIAN.SKIN:WASH AFFECTED AREAS W/SOAP &
WATER.REMOVE CONTAMINATED CLOTHING.INGESTION:DRINK 1 OR 2
GLASSESOF WATER TO DILUTE.DO NOT INDUCE VOMITING.IF SPONTANEOUS
VOMITING OCCURS KEEP HEAD AT OR BELOW KNEE LEVELTO PREVENT
ASPIRATION INTO LUNGS.CONSULT PHYSICIAN IMMDD

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F 40.56C
Lower Limits:1.0
Extinguishing Media:FOAM, CARBON DIOXI
DE CO2, DRY CHEMICAL, WATER MIST.
Fire Fighting Procedures:SMOTHER FLAMES W/ONE OF THE ABOVE
EXTINGUISHING MEDIA.WATER MAY BE USED TO COOL DOWN UNOPENED
CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT.DO NOT USE IN
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.WEAR
APPROPRIATE PERSONAL PROTECTION EQUIP & APPROVED RESPIR
ATOR.
CONTAIN SPILL W/ABSORBENT MATERIAL & PUT INTO VAPOR TIGHT
CONTAINERS.PREVENT MATERIAL FROM CONTACTIN G ANY WTR SOURCES OR
SEWERS LEADING TO SURFACE WTR

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS DESIGNED TO COMPLY
W/ANSI/NFPA 30 FLAMMABLE & COMBUSTIBLE LIQUIDS CODE.
Other Precautions:GROUND CONTAINERS WHEN POURING LIQS/PDRS TO AVOID
STATIC CHARGE BUILD UP.DO NOT HANDLE UNTIL MANUFACTURERS SAFETY

PRECAUTIONS HAVE BEEN READ & UNDERSTOOD. PROVIDE ADEQUATE VENTILATION OR RESPIRATORY PROTECTION TO REMOVE DECOMPOSITION PROD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN OUTDOOR OR OPEN AREAS, USE APPROVED RESPIRATOR. IN RESTRICTED VENTILATION AREAS USE APPROVED RESPIRATOR TO REMOVE A COMBINATION OF PARTICLES & VAPOR.

Ventilation: YES

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY EYE WEAR TO PROTECT FROM SPLASH

Other Protective

Equipment: PREVENT PROLONGED SKIN CONTACT W/CONTAMINATED CLOTHING.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 148 - 323F

Vapor Density: >AIR

Evaporation Rate & Reference: