View NSN Online: https://aerobasegroup.es/nsn/8010-00-527-2045

Product ID: ENAMEL ALKYD GLOSS, COMP L YELLOW 13538 MSDS Date:07/31/1987 FSC:8010 NIIN:00-527-2045 **MSDS Number: BHQTJ** === Responsible Party === Company Name: CON-LUX COATINGS, INC. Address:226 TALMAGDE ROAD Box:847 City:EDISON State:NJ ZIP:08818-0847 Country:US Info Phone Num:(206) 287-4000 Emergency Phone Num: (206) 287-4000 CAGE:60189 === Contractor Identification === Company Name: CON-LUX COATINGS INC Address:226 TALMADGE RD Box:847 City:EDISON State:NJ ZIP:08818-0847 Country:US Phone:732-287-4000 CAGE:60189

Ingred Name:MINERAL SPIRITS VAPOR PRESSURE 2 MMHG @ 20C CAS:64742-47-8 RTECS #:SE7555000 Fraction by Wt: >1% OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #: XR2275000 Fraction by Wt: >1% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:LEAD CHROMATE CAS:1334-37-2 RTECS #:GB2975000 Fraction by Wt: >1% ACGIH TLV:.05PB .1CR03 MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Effects of Overexposure:EYE/SKIN: IRRITATION MAY OCCUR WITH OVEREXPOSURE. INHALATION: MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHES, DIZZINESS, NAUSEA.

First Aid:EYE:FLUSH IMMEDIATELY W/COPIOUS QTY'S OF WTR FOR 15 MINS.CONSULT A PHYSICIAN. SKIN:WASH AFFECTED AREAS W/SOAP & WTR.REMOVE CONTAMINATED CLOTHING. INHALATION:REMOVE TO FRESH AIR. RESTORE RESPIRATION IF NECESSARY.CONSULT PHYSICNINGESTION: DONOT INDUCE VOMITING. DRINK 1-2 GLASSES OF WATER TO DILUTE.

Flash Point Method:TCC Flash Point:105F/4 0.56C Lower Limits:1.0 Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED CONTAINERS IN VICINITY. Unusual Fire/Explosion Hazard:DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT. CONTAINS FLAMMABLE SOLVENT.

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL

WITH ABSORBENT MATL & PUT INTO VAPOR TIGHT CONTAINERS. PREVENT MATERIAL FROM CONTACTING ANY WATER SOURCESOR SEWERS LEADING TO SURFACE WATERS.

Handling and Storage Precautions: STORE IN AREAS DESIGNED TO COMPLY WITH ANSI/NFPA30FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE. Other Precautions: GROUND CONTAINERS WHEN POURING LIQUIDS & POWDERS TO AVOID STATIC CHARGE BUILD UP ======= Exposure Controls/Personal Prote ction =========== Respiratory Protection: IN OUTDOORS, OPEN, OR RESTRICTED VENTILATED AREAS USE APPROVED RESPIRATOR. Ventilation:SUFFICIENT VENTILATION Protective Gloves: IMPERVIOUS TYPE REQUIRED FOR LONG EXPSR Eye Protection: SAFETY GLASSES Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM FACILITS. Supplemental Safety and Health NK ========= Physical/Chemical Pro perties ================ Boiling Pt:B.P. Text:148-323F Vapor Density:> AIR Evaporation Rate & amp; Reference: SLOWER THAN ETHER Percent Volatiles by Volume:60.15

Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS Stability Condition to Avoid:EXTREME HEAT, SPARKS, OR OPEN FLAMES Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice t o verify and

assume responsibility for the suitability of this information to their particular situation.