

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS BLK 17038, ID 742702 -- 8010-00-527-2050

===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS BLK 17038, ID 742702

MSDS Date:01/06/1988

FSC:8010

NIIN:00-527-2050

MSDS Number: BHQTK

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:31

6-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LIGROIN (PETROLEUM HYDROCARBON MIXTURE)

CAS:8032-32-4

RTECS #:OF6180000

OSHA PEL:500 PPM/2950 MG/CU.M

ACGIH TLV:100 PPM/525 MG/CU.

M.

Ingred Name:MINERAL SPIRITS
VAPOR PRESSURE 2 MMHG @ 20C
CAS:64475-85-0
RTECS #:PY8240000
OSHA PEL:500 PPM/2950 MG/CU.M
ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GL LESS WATER & NPRS* 480 G/L LESS
WATER VOC 10.4 LB/GAL SOLIDS 1248 G/L SOLIDS CALCULATED.
RTECS #:99999999VO

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

===== Hazards Identification =====

Rout
es of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED
PROLONGED/REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTSWITH
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY
DELIBERATELYCONCENTRATING & INHALING THE CONTENTS MA Y BE HARMFUL
OR FATAL. HIGH CONCENT. MAYCAUSE CNTRL NERVS. SYS. DEPRESS. CHARAC.
BY HDACHES,DIZZINESS,NAUSEA,& CONFUSION
Effects of Overexposure:EYE: MAY CAUSE IRRITATION; SKIN: MAY CAUSE
D
EFATTING & IRRITATION OF THE SKIN.; INHALATION: MAY CAUSE NOSE OR
THROAT IRRITATION.; INGESTION: CAN CAUSE GASTROIN-TESTINAL
IRRITATION, NAUSEA, & VOMITING. ASPIRATION OF MATL INTO LUNGS MAY
CAUSECHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER, LIFTING UPPER/LOWER LIDS OCCASIONALLY.
FOR 15 MINS. GET MED.ATTENTION.; SKIN: REMOVE CONTAMINATED
CLOTHING. WAS AFFECTED AREA W/SOAP & WATERO

BTAIN MEDICAL ATTENTION

IF IRRITATION P ERSISTS.; INGESTION: CALL HOSPITAL EMERGENCY, OR
PHYSICIAN IMMEDIATELY.; INHALATION: REMOVE TO FRESH AIR IMMEDIATELY
ANDGIVE ARTIFICIAL RESP. IF NOT BREATHING. KEEP WARM & QUIET.GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:102F/38.89C

Extinguishing Media:USE NFPA CL.B FIRE EXTINGUISHERS (CARBON
DIOXIDE,DRY CHEM., ALCOHOL FOAM).POLYMER FOAM IS PREFERRED F
OR
LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE,BUT MAY BE USED TO
COOL EXPSD CONTNRS TO PREVENT PRESS.BUILDUP/POSSIBLE IGNT./EXPLSN
W/EXPSD TO EXTRM HEAT,FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE
FROM HEAT, ELEC. EQUIP., SPARKS, AND FLAME. CLOSED CONTAINERS
MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WEAR S.C.B.A.

===== Accidental Release Measures =====

Spill Release Proce

dures:KEEP SPECTATORS AWAY, & ELIMINATE ALL IGNITION
SOURCES. DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER TO
COVERED METAL CONTNR FOR RECOVERY OR DISPOSAL. USE ONLY NON
SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29 CFR 1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINERS AFTER EACH
USE. CONTAINERS SHOULD
BE GROUNDED & BONDED TO THE RECEIVING
CONTAINER. EMPTY CONTAINERS MUST NOT BE WASHED OR REUSED FOR
ANY PURPOSE.DONOT W ELD,BRAZE/CUT ON EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED MECHANICAL FILTER RESPIRATOR
FOR OUTDOOR OR OPEN VENTILATED AREAS. USE NIOSH APPROVED AIR
SUPPLIED RESPIRATOR FOR CONFINED AREAS.

Ventilation:GEN. DIL. & LO. EXH. VENT. IN SUFF. VOL. REMOVE DECOMP.
PRODTHAT ARE G

EN. W/WLDNG,CUTNG,BRZNG OBJECT COATED W/THIS PROD.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:NONE NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280-388F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/M

aterials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL REGULAT
IONS. DO NOT INCINERATE CLOSED CONTNRRRCRA
CLASSIFICATION DOO1.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility
for the suitability of this information to their
particular situation.