

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS BLK 17038, ID 742702 -- 8010-00-527-2050

===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS BLK 17038, ID 742702

MSDS Date:01/06/1988

FSC:8010

NIIN:00-527-2050

MSDS Number: BHQTK

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:31

6-733-1361

Preparer's Name:W.A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LIGROIN (PETROLEUM HYDROCARBON MIXTURE)

CAS:8032-32-4

RTECS #:OF6180000

OSHA PEL:500 PPM/2950 MG/CU.M

ACGIH TLV:100 PPM/525 MG/CU.

M.

Ingred Name:MINERAL SPIRITS  
VAPOR PRESSURE 2 MMHG @ 20C  
CAS:64475-85-0  
RTECS #:PY8240000  
OSHA PEL:500 PPM/2950 MG/CU.M  
ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GL LESS WATER & NPRS\* 480 G/L LESS  
WATER VOC 10.4 LB/GAL SOLIDS 1248 G/L SOLIDS CALCULATED.  
RTECS #:99999999VO

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

===== Hazards Identification =====

Rout  
es of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:REPORTS HAVE ASSOCIATED  
PROLONGED/REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTSWITH  
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY  
DELIBERATELYCONCENTRATING & INHALING THE CONTENTS MA Y BE HARMFUL  
OR FATAL. HIGH CONCENT. MAYCAUSE CNTRL NERVS. SYS. DEPRESS. CHARAC.  
BY HDACHES,DIZZINESS,NAUSEA,& CONFUSION  
Effects of Overexposure:EYE: MAY CAUSE IRRITATION; SKIN: MAY CAUSE  
D  
EFATTING & IRRITATION OF THE SKIN.; INHALATION: MAY CAUSE NOSE OR  
THROAT IRRITATION.; INGESTION: CAN CAUSE GASTROIN-TESTINAL  
IRRITATION, NAUSEA, & VOMITING. ASPIRATION OF MATL INTO LUNGS MAY  
CAUSECHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER, LIFTING UPPER/LOWER LIDS OCCASIONALLY.  
FOR 15 MINS. GET MED.ATTENTION.; SKIN: REMOVE CONTAMINATED  
CLOTHING. WAS AFFECTED AREA W/SOAP & WATERO

BTAIN MEDICAL ATTENTION

IF IRRITATION P ERSISTS.; INGESTION: CALL HOSPITAL EMERGENCY, OR  
PHYSICIAN IMMEDIATELY.; INHALATION: REMOVE TO FRESH AIR IMMEDIATELY  
ANDGIVE ARTIFICIAL RESP. IF NOT BREATHING. KEEP WARM & QUIET.GET  
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:102F/38.89C

Extinguishing Media:USE NFPA CL.B FIRE EXTINGUISHERS (CARBON  
DIOXIDE,DRY CHEM., ALCOHOL FOAM).POLYMER FOAM IS PREFERRED F  
OR  
LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE,BUT MAY BE USED TO  
COOL EXPSD CONTNRS TO PREVENT PRESS.BUILDUP/POSSIBLE IGNT./EXPLSN  
W/EXPSD TO EXTRM HEAT,FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE  
FROM HEAT, ELEC. EQUIP., SPARKS, AND FLAME. CLOSED CONTAINERS  
MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WEAR S.C.B.A.

===== Accidental Release Measures =====

Spill Release Proce

dures:KEEP SPECTATORS AWAY, & ELIMINATE ALL IGNITION  
SOURCES. DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER TO  
COVERED METAL CONTNR FOR RECOVERY OR DISPOSAL. USE ONLY NON  
SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE  
QUANTITIES IN COMPLIANCE WITH OSHA 29 CFR 1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINERS AFTER EACH  
USE. CONTAINERS SHOULD  
BE GROUNDED & BONDED TO THE RECEIVING  
CONTAINER. EMPTY CONTAINERS MUST NOT BE WASHED OR REUSED FOR  
ANY PURPOSE.DONOT W ELD,BRAZE/CUT ON EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED MECHANICAL FILTER RESPIRATOR  
FOR OUTDOOR OR OPEN VENTILATED AREAS. USE NIOSH APPROVED AIR  
SUPPLIED RESPIRATOR FOR CONFINED AREAS.

Ventilation:GEN. DIL. & LO. EXH. VENT. IN SUFF. VOL. REMOVE DECOMP.  
PRODTHAT ARE G

EN. W/WLDNG,CUTNG,BRZNG OBJECT COATED W/THIS PROD.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:NONE NEEDED

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:280-388F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/M

aterials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE/DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND  
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,  
AND LOCAL REGULAT  
IONS. DO NOT INCINERATE CLOSED CONTNRRRCRA  
CLASSIFICATION DOO1.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility  
for the suitability of this information to their  
particular situation.