

PRATT AND LAMBERT INC -- ENAMEL,ALKYD,LUST BLACK 37038,ID-741702 -- 8010-00-297-0546

===== Product Identification =====

Product ID:ENAMEL,ALKYD,LUST BLACK 37038,ID-741702

MSDS Date:03/01/1986

FSC:8010

NIIN:00-297-0546

MSDS Number: BHRGW

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:6119

6

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty

:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:VOC. ORGANIC CMPD 4.1 LB/GL LESS WATER & NPRS* 492 G/L
LESSWATER VOC 8.7 LB/GAL SOLIDS 1044 G/L SOLIDS CALCULATED.
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:REPEATED EXPOSURE TO CRYSTALLINE
SILICA MAY CAUSE PNEUMOCONIOSIS,A PROGRESSIVELYDISABLING LUNG
DISEASE. REPORTS HAVE ASSOCIATED PROLONGED/REPEATED OC
CUPATIONAL
OVEREXPOSURE TO SOLVENTS W PERMANENT BRA IN & NERVOUS SYSTEM
DAMAGE. INTENTIONALMISUSE BY DELIBERATELY CONCENTRATING/INHALING
THE CONTENTS MAYBE HARMFUL/FATAL
Effects of Overexposure:INHL:ANESTHETIC MAY CAUSE IRRITATION OF THE
NOSE,THROAT,ACUTE NERVOUS AND SYSTEMDEPRESSION.CHARACTERIZED BY
HDACHE,DIZZINESS,CONFUSION,NAUSEA,UNCONSCIOUSNESS & ASPHYXIATION.
EYE/SKIN:EYE IRRITATION,DE FATTING AND SKIN IRRITATION.
SWALLOWING:GASTROINTESTINAL IRRITATION,NAUSEA,VO

MITING,DIARRHEA,OR
CHEMICAL PNEUMONITIS.
Medical Cond Aggravated by Exposure:NONE CURRENTLY KNOWN

===== First Aid Measures =====

First Aid:INHL: REMOVE TO FRESH AIR IMMEDIATELY.IF BREATHING HAS STOPPED,GIVE ARTIFICIAL RESPIRATION.KEEP WARM & QUIET.EYE:FLUSH W/WATER LIFTING UPPER/LOWER LIDS OCCASIONALLY FOR 15MINS.SKIN:WASH AFFECTED AREA W/SOAP & WATER.SWALLOWING:INDUCE VOMITING IMMEDIATELY BY GIVING TWO GLASSES OF WATER & STICKING FINGER DOWN THROAT. GET MEDICAL ATTENTION IMMEDIATELY.NEVER GIVE AN UNCONSCIOUS PERSON ANYTHING.

===== Fire Fighting Measures =====

Flash Point:80F/26.67C
Extinguishing Media:USE NFPA,CLASS B,FIRE EXTINGUISHERS (CARBON DIOXIDE,DRY CHEMICAL,ALCOHOL FOAM)DESIGNED TO EXTINGUISH FLAMMABLE LIQ. FIRE
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS.WATER MAYBE INEFFECTIVE,MAYBE USED TO COOL EXPOSED CONTAINERS.IF WATER IS USED,FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS ANDFLAMES.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY.ELIMINATE ALL IGNITION SOURCEDIKE & CONTAIN SPILL W/INERT MATERIAL.TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL,REMOVE W/INERT ABSORBE NT.USE ONLY NON- SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DONOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106. CONTAINERS SHOULD BE GROUNDED/BONDED TO THE RECEIVING CONTNR.
Other Precautions:DONOT TAKE INTERNALLY.CLOSE CONTAINER AFTER EACH USE.DONOT BREATHE SANDING DUST.EMPTY CONTAINERS MUST NOT BE WASHED & REUSED FOR ANY PURPOSE.DONOT WELD/BRAZE ORCUT ON EMPTY CON

TAINER.NEVER USE PRESSUR E TO EMPTY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING OUTDOORS,IN OPEN OR WELL VENTILATED AREAS,USE NIOSH APPROVED MECH ANICAL FILTER RESPIRATOR TO REMOVE OVERSPRAY.IN RESTRICTED VENTILATION AREAS,USE NIOSH APPROVED PAINT SPRAY REPIRATOR TO REMOVE SPRAY MIST & ORGANIC VAPORS.

Ventilation:PROVIDE GENERAL DILUTION & LOCAL EXHAUSE VENTILATION IN SUFFICIENT VOLUME.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES

Eye Protection:SAFETY SPECTACLES W/SIDE SHIELDS

Other Protective Equipment:NONE

Work Hygienic Practices:NONE

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:244-399F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

OR ALKALINE MATERIALS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:BURNING,INCLUDING WHEN HEATED BY WELDING/CUTTING,WILL PRODUCE SMOKE,CARBON MONOXIDE AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL,LOCAL,& STATE LAWS INCINERATE ONLY IN EPA FACILITY.DONOT INCINERATE CLOSED CONTAINERS.OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.CONTAMINATED ABS

ORBANT MAY BE DISPOSED IN A HAZARDOUS
WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the
suitability of this information to their
particular situation.