Product ID:TT-E-509B SEMI GLOSS ENAMEL MSDS Date:11/01/1988 FSC:8010 NIIN:00-225-7962 **MSDS Number: BHVZS** === Responsible Party === Company Name:S.L. GILLMAN PAINT COMPANY Address:2250 MORELAND AVE. SE Box:NA **City:ATLANTA** State:GA ZIP:30315 Country:US Info Phone Num:404-622-1326 OR 404-589-4400 Emergency Phone Num:404-589-4400 OR 404-622-1326 CAGE:OO 269 === Contractor Identification === Company Name: GILLMAN PAINT CO. Address:2250 MORELAND AVE., S.E. **City:ATLANTA** State:GA ZIP:30315 Country:US Phone:404-622-1326 CAGE:GILLM Company Name:S.L. GILLMAN PAINT COMPANY Address:2250 MORELAND AVENUE, S.E. City:ATLANTA Phone:404 622 1326 CAGE:00269

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 40-45% OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:EYES:SEVERE IRRI,RED,TEAR,BLURRED VISION.SKIN:PROLONG/REPEATED CONTACT CAN CAUSEMOD IRRI,DEFATT,DERMATITIS. BREATH:EXCESSIVE INHALE OF VAPORS MAY CAUSE NASAL & RESPIRATORY IRRI,DIZZ,WEAK,FATIGUE,NAUSE A,HEADACHE,UNCONSC,ASPHYXIATION.INGEST:GASTRO IRRI,NAUSEA,VOMIT,&DIARRHEA.ASPIRATION INTO LUNGS CAUSE CHEM PNE

UMONHITIS

Effects of Overexposure:EYES:SEVERE IRRI,RED,TEAR,BLURRED VISION.SKIN:PROLONG/REPEATED CONTACT CAN CAUSEMOD IRRI,DEFATT,DERMATITIS. BREATH:EXCESSIVE INHALE OF VAPORS MAY CAUSE NASAL & RESPIRATORY IRRI,DIZZ,WEAK,FATIGUE,NAUSE A,HEADACHE,UNCONSC,ASPHYXIATION. INGEST:GASTRO IRRI,NAUSEA,VOMIT,&DIARRHEA.ASPIRATION INTO LUNGS CAUSE CHEM PNEUMONHITIS

Medical Cond Aggravated by Exposure:NONE EXPECTED.

First Aid:SKIN:THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. REMOVE CONTAM CLOTHES, LAUNDERBEFORE RE-USE. GET MED ATTN. EYES: WASH W/LRG AMTS OF WATER, LIFTING LIDS. GET MED ATTN. INGESTION: DO NOT INDUCE VOMIT, KEEP PERSON WARM AND QUIET. GET MEDATTN. VOMIT CAN CAUSE CHEM PNEUMONITIS, CAN BE FATAL. BREATH:REMOVE TO FRESH AIRBREATH DIFF ADMIN OXYGEN, BREATH STOPPED GIVE CPR, GET MED ATTN. KEEP WARM/QUIET

====

Flash Point Method:TCC
Flash Point:105 F/ 41 C
Lower Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARTUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND/OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES. WATER SPRAY INEFFECTIVE
Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR MAY TRAVEL ALONG GROUND/BY VENT, IGNITE BY FLAME, SPARK, OTHER IGNITE SOURCE AT LOCATIONS DISTANT. OVEREXP TO DECOMP MAY CAUSE HEA

LTH HZD

Spill Release Procedures: ELIM ALL SOURCES OF IGNITION; FLARES, FLAMES, ELECSPARKS. SM: ABSORB LIQ ON PAPER, VERMICULITE, FLOORABSORB & TRANS TO HOOD. LRG: WEAR PROTECTIVE EQUIPSTOP SPILL AT SOURCE, DIKE AREA, PUMP LIQ INTO SAL VAGE TANK.PREVENT RUN-OFF TO SEWERS, STREAMS, ETC.

Handling and Storage Precautions: AVOID STORING NEAR HIGH TE MPERATURES

OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN & AWAY FROM HEAT. DO NOT WELD OR FLAME-CUT AN EMPTY DRUM.

Other Precautions:DRUMS SHOULD BE GROUNDED & BONDED WHEN POURING. AVOID BREATHING SANDING DUST. KEEP CLOSURE TIGHT & CONTAINER UPRIGHT TO PREVENT LEAKAGE. DON'T STORE/USE NEAR SPARK,FLAME,ETC. EMPTY CONTAINER CONTAIN RESIDUE ALL HAZARD PRECAUTIONS REQUIRED

Respiratory Protection:TLV OF PRODUCT I

S EXCEEDED, NIOSH/MSHA JOINTLY

APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIR CONTROL. OSHA REG ALSO PERMIT OTHER NIOSH/MSHA RSPRT UNDER SPEC CONDITION. SEE SAF ETY EQUIP SUPPLIER. ENGIN/ADMIN CONTROLS

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST VENTILATION) TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NITRILE RUBBER GLOVES OR NEOPRENE GLOVES Eve Protection:CHEMICAL SPLASH GOGGLES, OSHA REGULATED

Other Protective Equipme

nt:TO PREVENT REPEATED/PROLONGED SKIN CONTACT,

WEAR IMPERVIOUS CLOTHING/BOOTS. OTHER TYPES OF SAFETY GLASSES ARE PERMITTED.

Work Hygienic Practices: AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. WASH HANDS BEFORE EATING OR USING WASHROOM, SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH S.L. GILLMAN OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADV ANCE OF NEED THAT THE I NFORMATION IS CURRENT, APPLICABLE, ANDSUITABLE TO THEIR CIRCUMSTANCES.

Boiling Pt:B.P. Text:300 F Vapor Density:> THAN AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:65.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:AVOID HIGH TEMPERATURES , OPEN FLAME AND SPARKS. CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS SUCH AS; CARBON DIOXIDE, CARBON MONOXIDE, AND VARIOUS HYDROCARBONS.

Waste Disposal Methods: IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this

information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.