

S.L. GILLMAN PAINT COMPANY -- TT-E-509B SEMI GLOSS ENAMEL -- 8010-00-225-7962

===== Product Identification =====

Product ID:TT-E-509B SEMI GLOSS ENAMEL

MSDS Date:11/01/1988

FSC:8010

NIIN:00-225-7962

MSDS Number: BHVZS

=== Responsible Party ===

Company Name:S.L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVE. SE

Box:NA

City:ATLANTA

State:GA

ZIP:30315

Country:US

Info Phone Num:404-622-1326 OR 404-5

89-4400

Emergency Phone Num:404-589-4400 OR 404-622-1326

CAGE:OO269

=== Contractor Identification ===

Company Name:GILLMAN PAINT CO.

Address:2250 MORELAND AVE., S.E.

City:ATLANTA

State:GA

ZIP:30315

Country:US

Phone:404-622-1326

CAGE:GILLM

Company Name:S.L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVENUE, S.E.

City:ATLANTA

Phone:404 622 1326

CAGE:OO269

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Frac

tion by Wt: 40-45%
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:EYES:SEVERE IRRI,RED,TEAR,BLURRED
VISION.SKIN:PROLONG/REPEATED CONTACT CAN CAUSEMOD
IRRI,DEFATT,DERMATITIS. BREATH:EXCESSIVE INHALE OF VAPORS MAY CAUSE
NASAL & RESPIRATORY IRRI,DIZZ,WEAK,FATIGUE,NAUSE
A,HEADACHE,UNCONSC,ASPHYXIATION.INGEST:GASTRO
IRRI
,NAUSEA,VOMIT,&DIARRHEA.ASPIRATION INTO LUNGS CAUSE CHEM
PNEUMONHITIS
Effects of Overexposure:EYES:SEVERE IRRI,RED,TEAR,BLURRED
VISION.SKIN:PROLONG/REPEATED CONTACT CAN CAUSEMOD
IRRI,DEFATT,DERMATITIS. BREATH:EXCESSIVE INHALE OF VAPORS MAY CAUSE
NASAL & RESPIRATORY IRRI,DIZZ,WEAK,FATIGUE,NAUSE
A,HEADACHE,UNCONSC,ASPHYXIATION. INGEST:GASTRO
IRRI,NAUSEA,VOMIT,&DIARRHEA.ASPIRATION INTO LUNGS CAUSE CHEM
PNEUMONHITIS
Medical Cond Aggravated by Exposure:NONE EXPECTED.

=====
===== First Aid Measures =====

First Aid:SKIN:THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. REMOVE
CONTAM CLOTHES, LAUNDERBEFORE RE-USE. GET MED ATTN. EYES: WASH
W/LRG AMTS OF WATER, LIFTING LIDS. GET MED ATTN. INGESTION: DO NOT
INDUCE VOMIT , KEEP PERSON WARM AND QUIET. GET MEDATTN. VOMIT CAN
CAUSE CHEM PNEUMONITIS, CAN BE FATAL. BREATH:REMOVE TO FRESH
AIRBREATH DIFF ADMIN OXYGEN, BREATH STOPPED GIVE CPR, GET MED ATTN.
KEEP WARM/QUIET

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105 F/ 41 C
Lower Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARTUS WITH
FULL FACEPIECE OPERATED IN PRESSURE-DEMAND/OTHER POSITIVE PRESSURE
MODE WHEN FIGHTING FIRES. WATER SPRAY INEFFECTIVE
Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR MAY TRAVEL ALONG
GROUND/BY VENT, IGNITE BY FLAME, SPARK, OTHER IGNITE

SOURCE AT

LOCATIONS DISTANT. OVEREXP TO DECOMP MAY CAUSE HEALTH HZD

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL SOURCES OF IGNITION; FLARES, FLAMES, ELECSPLARKS. SM: ABSORB LIQ ON PAPER,VERMICULITE, FLOORABSORB & TRANS TO HOOD. LRG: WEAR PROTECTIVE EQUIPSTOP SPILL AT SOURCE, DIKE AREA, PUMP LIQ INTO SAL VAGE TANK.PREVENT RUN-OFF TO SEWERS, STREAMS, ETC.

===== Handling and Storage =====
===

Handling and Storage Precautions:AVOID STORING NEAR HIGH TEMPERATURES OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN & AWAY FROM HEAT. DO NOT WELD OR FLAME-CUT AN EMPTY DRUM.

Other Precautions:DRUMS SHOULD BE GROUNDED & BONDED WHEN POURING. AVOID BREATHING SANDING DUST. KEEP CLOSURE TIGHT & CONTAINER UPRIGHT TO PREVENT LEAKAGE. DON'T STORE/USE NEAR SPARK,FLAME,ETC. EMPTY CONTAINER CONTAIN RESIDUE ALL HAZARD PRECAUTIONS REQUIRED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:TLV OF PRODUCT IS EXCEEDED, NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIR CONTROL. OSHA REG ALSO PERMIT OTHER NIOSH/MSHA RSPRT UNDER SPEC CONDITION. SEE SAF ETY EQUIP SUPPLIER. ENGIN/ADMIN CONTROLS

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST VENTILATION) TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NITRILE RUBBER GLOVES OR NEOPRENE GLOVES

Eye Protection:

CHEMICAL SPLASH GOGGLES, OSHA REGULATED

Other Protective Equipment:TO PREVENT REPEATED/PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING/BOOTS. OTHER TYPES OF SAFETY GLASSES ARE PERMITTED.

Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. WASH HANDS BEFORE EATING OR USING WASHROOM, SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH S.

L. GILLMAN OR NOT.

RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300 F

Vapor Density:> THAN AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:65.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HIGH TEMPERATURES, OPEN FLAME AND SPARKS. CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS SUCH AS; CARBON DIOXIDE, CARBON MONOXIDE, AND VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:IF RUN-OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED, THAT A SPILL HAS OCCURED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.