View NSN Online: https://aerobasegroup.es/nsn/8010-00-926-1488

Product ID:PAINT STRIPPER 7 (MIL-R-81294C) OR B

MSDS Date:01/02/1988

FSC:8010

NIIN:00-926-1488

MSDS Number: BHWCK === Responsible Party ===

Company Name: CREST INDUSTRIAL CHEMICAL

Address:6341 BEVERLY HILL

City:HOUSTON

State:TX ZIP:77057 Country:US

Info Phone Num:780-1828

Emergen

cy Phone Num:780-1828

CAGE:77513

=== Contractor Identification ===

Company Name: CREST INDUSTRIAL CHEMICALS INC

Address:6341 BEVERLY HILL

Box:42242

City:HOUSTON

State:TX

ZIP:77057-6500 Country:US

Phone:713-780-1828

CAGE:77513

======= Composition/Information on Ingredients ========

Ingred Name: METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: SODIUM CHROMATE (SARA

OSHA PEL:0.1 PPM CRO3;CEILING ACGIH TLV:0.05 MG CR/M3; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS
Ingred Name:PHENOLIC BODIES ACGIH TLV:5 PPM (SKIN)
========= Hazards Identification ===========
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION OF NOSE AND EYES, SLIGHT NARCOSIS.
======================================
First Aid:SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH WITH WATER, OBTAIN MEDICAL ATTENTION.
======================================
Flash Point Method:COC Flash Point:NONE Extinguishing Media:CARBON DIOXIDE OR CHEMICAL FOAM. Fire Fighting Procedures:THERMAL DECOMPOSITION WILL PRODUCE TOXIC OXIDES OF CHLORINE WEAR GAS MASKS.
========= Accidental Release Measures ==========
Spill Release Procedures:VENTILATE AREA. MOP UP SPILLAGE AND DISPOSE OF I.A.W. LOCAL, STATE AND FEDERAL REGULATIONS.
=========== Handling and Storage ============
Handling and Storage Precautions:TRANSPORT AND STORE IN CLOSED CONTAINERS AT TEMPERATURES UP TO 110 F. Other Precautions:DO NOT STORE IN DIRECT RAYS OF SUN, OPEN CONTAINERS CAREFULLY TO AVOID SPRUTING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:FRESH AIR

III) CAS:7775-11-3

RTECS #:GB2955000

MASK. Ventilation:USE LOCAL EXHAUST. Protective Gloves:USE PROTECTIVE GLOVES. Eye Protection:USE EYE PROTECTION. Other Protective Equipment:USE SOLVENT RESISTANT APRONS. Supplemental Safety and Health NK
========== Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:110 F Melt/Freeze Pt:M.P/F.P Text:80% Vapor Pres:350 MM Vapor Density:> 1(AIR=1) Spec Gravity:1.10 (H20=1) Evaporation Rate & Description (BUTYL ACETATE=1) Solubility in Water:APPRECIABLE Appearance and Odor:VISCOUS YELLOW LIQUID PHENOLIC ODOR.
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZERS. Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL PRODUCE TOXIC OXIDES OF CHLORINE.
======== Disposal Considerations ===========
Waste Disposal Methods:TREAT FOR PHENOLIC BODIES AND CHROMATE, DISPOSE OFI.A.W. LOCAL, STATE AND FEDERAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department.

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.