View NSN Online: https://aerobasegroup.es/nsn/8010-00-527-3199

Product ID: ENAMEL ALKYD GLOSS RED 11136, ID 742114 MSDS Date:05/24/1985 FSC:8010 NIIN:00-527-3199 MSDS Number: BHWSW === Responsible Party === Company Name: PRATT & LAMBERT, INC. Box:2153 **City:WICHITA** State:KS ZIP:67201 Country:US Info Phone Num:316-733-1361 **Emergency Phone Num:31** 6-733-1361 Preparer's Name:W.A. ELLISON CAGE:FO127 === Contractor Identification === Company Name: PRATT & LAMBERT, INC/BUFFALO, NY 14240 Box:22 CAGE:FO127 Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:MOLYBDATE ORANGE CAS:12656-85-8 RTECS #:QA4660000 Fraction by Wt: 10-20%

Ingred Name:METHYL ETHYL KETOXIME (VAPOR PRESSURE 10 MMHG @ 20C) RTECS #:PM7783000 Fraction by Wt: 0.5%

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 3.20 MMHG @ 20C) CAS:64742-88-7 Fraction by Wt: 40-50% ACGIH TLV:500 PPM

Ingred Name:VOC. ORGANIC CMPD 4.0 LB/GL LESS WATER & NPRS\* 480 G/L RTECS #:9999999VO

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF NOSE,THROAT,EYES & POSS
IBLE DIZZINESS, & NAUSEA. SPRAY MISTS
CONTAIN LEAD. LEAD POISONING IS CHARACTERIZED BY THE FOLLOW-ING PROGRESSIVE STEPS: HEADACHES, DIZZIN ESS,STAGGERING GAIT, CONFUSION, COMA, ORUNCONSCIOUSNESS.

First Aid:EYE:FLUSH IMMEDIATELY W/LG AMOUNTS OF WTR FOR 15 MINS.
SKIN:REMOVE CONTAMINATED CLOTHING & WASH ALL
AFFECTED AREA W/WATER. INHALATION:REMOVE FROM EXPOSURE
& PROVID E FRESH AIR.INGE
STION: DO NOT INDUCE VOMITING. CONSULT A
PHYSICIAN IMMEDIATELY IN ALL CASES.

Flash Point Method:TCC

Flash Point:104F/40.00C

Lower Limits:1.10

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM, POLYMER FOAM.

Fire Fighting Procedures:S.C.B.A. SHOULD BE AVAILABLE FOR FIREFIGHTERS. WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD UP.

Unusual Fire/Explosion

Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT,ELEC EQUIP.,SPARKS, & OPEN FLAME. CLOSED CONTNRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITIONS. REMOVE W/INERT ABSORBENT & NON SPARKING TOOLS. STEPS MUST BE TAKEN TO PREVENT CONTAMINATION OF GROUND WATER OR STREAMS.

Handling and

Storage Precautions:DONOT STORE ABOVE 120F. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINERS.

Respiratory Protection:USE MECHANICAL RESPIRATOR IN OUTDOOR/OPEN AREAS. CHEMICAL-MECHANICAL FILTERS FOR RESTRICTED VENTILATION AREAS. Ventilation:GENERAL DILUTION OR LOCAL EXHAUST Protective Gloves:SOLVENT EMPERMEABLE Eye Protection:SAFETY GLASS ES Other Protective Equipment:PROTECTIVE EQUIPMENT TO PREVENT SKIN CONTACT Supplemental Safety and Health NK

Boiling Pt:B.P. Text:311-373F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:62

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS Stability Condition to Avoid:FIRES, HEAT  , AND HOT SURFACES
 Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE AND OXIDES OF CARBON & LEAD.
 Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIVE CHEMICALS W/O TECHNICAL SUPER-VISION.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONT- AINERS.

Disclaimer (provided with this information by the compiling agencies): Th

is information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.