

PRATT & LAMBERT, INC. -- LAC SPRAYING RED 11105 ID793102 -- 8010-00-577-4524

===== Product Identification =====

Product ID:LAC SPRAYING RED 11105 ID793102

MSDS Date:12/15/1988

FSC:8010

NIIN:00-577-4524

MSDS Number: BHYJP

==== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Prepa

rer's Name:W.A. ELLISON

CAGE:FO127

==== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA
(VP 40 MM HG @ 20 DEG. C)

CAS:8030-30-6

RTECS #:DE3030000

OSHA PEL:500 PPM

ACGIH TLV:300 PPM 1350 MG/CU.M

Ingred Nam

e:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE

(VAPOR PRESSURE 2 MM @ 20 DEG C)

CAS:108-65-6

RTECS #:AI8925000

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE

CAS:9004-70-0

RTECS #:QW0970000

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOBUTYL ACETATE

CAS:110-19-0

RTECS #:AI2025000

OSHA PEL:150 PPM 700 MG/CU M

ACGIH TLV:150 PPM 700 MG/CU M

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OS

HA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:VOC. ORGANIC CMPD 5.3 LB/GAL LESS WATER & NPRS* 636 G/L
LESS WATER VOC. 23.4 LB/GAL SOLIDS 2808 G/L SOLIDS CALCU
RTECS #:9999999VO

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: < 1%
Other REC Limits:LFL 1.0/UFL 8.0
OSHA PEL:500 PPM
ACGIH T
LV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VOC 5.33 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 640 G/L LESS WATER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 22.95 LB/GAL SOLIDS 2754 G/L SOLIDS
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:SWALLOWING: GASTROINTESTINAL

IRRITATION, NAUSEA,M AND VOMITING. ASPIRATION OF MATERIAL INTO LUNG
MAY CAUSE CHEMICAL PNEUMONITIS. INHALATION NOSE OR THROAT
IRRITATION. EYE: EYE IRRITATION. SKIN PRIMARY SKIN IRRITANT. MAY
CUSE SEVERE SKIN IRRITATION.

Explanation of Carcinogenicity:DI (2-ETHYLHEXYL) PHTHALATE IS LISTED AS
A POTENTIAL CARCINOGEN BY THE NTP.

Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED
OCCUPATIONAL OVEREXPOSURE TO SOL VENTS WITH PERMANENT BRAIN AND
NERVO

US SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== First Aid Measures =====

First Aid:SWALLOWING: IF SWALLOWED DO NOT INDUCE VOMITING. GET MED ATTN. INHALATION: REMO VE TO FRESH AIR IMMEDIATELY. GIVE CPR IF REQUIRED AND OBTAIN MED ATTN: EYE: FLUSH WITH WATER AT LEAST 15 MIN LIFTING UPP ER AND LOWER LIDS OCCASIONALLY. GET MEDATTN. SKIN: IMMEDIATELY FLUSH WTH CONTAM INATED AREA WITH LARGE AMOUNTS OF WATER.REMOVE CONTAMINATED CLOTHING AS WATER IS APPLIED. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:20F -6.67C
Extinguishing Media:NFPA CLASS B FIRE EXTING. DESIGNED TO EXTINGUISH FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP/AUTO IGNITION/EXPLOS.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY T IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. WARNING FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR RESPIRATORS, EYE, HAND, AND BODY PROTECTION APPROPRIATE FOR THE SIZE OF THE SPILL AND THE EXPOSURES ENCOUNTERED. KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION SOURCES.
DIKE AND CONTAIN SPILL. DO N OT CONTAMINATE WATER SOURCES.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT TAKE INTERNALLY. CLOSE AFTER USE. EMPTY CONTAINERS NOT TO BE RE USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED/BONDED TO REC CONTAINER. DO NOT WELD/BRAZE/CUT ON EMPTY CONTR. NEVER USE PRES SUR

E TO EMPTY. DRUM NOT PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: RESTRICTED VENTILATION AREAS A NIOSH APPROVE CHEMICAL CARTRIDGE RESPIRATOR MAY BE REQUIRED. CONDITIONS SUCH AS SPRAYING A MECHANICAL PREFILTER MAY ALSO BE REQUIRED. IN CONFINED AREAS USE A NIOSH/MSHA APPROVE AIR SUPPLIED RESPIRATOR.

Ventilation: GEN DILUTION AND LO EXHAUST VENT IN SUFFICIENT VOLUME /PATTERN TO MAINTAIN CONCENTRATIONS OF HAZ SUB BELOW EXP LIMITS

Protective Gloves: SOLVENT IMPERMEABLE GLOVES

Eye Protection: WEAR SAFETY SPECTACLES

Other Protective Equipment: EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 175 TO 302F

Vapor Density: > AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 77

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo

id: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN MAY BE GENERATED.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE ONLY IN EPA PERMIT

TED FACILITY. DO

NOT INCINERATE CLOSED CONTAINERS. CONTAMINATED ABSORBANT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL. DISPOSE ONLY IAW FED/ST/LO REGULATIONS. RCRA CLAS SIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.