

MALTER INTERNATIONAL -- CORROSION PREVENTIVE COMPOUND -- 8030-00-938-1947

===== Product Identification =====

Product ID:CORROSION PREVENTIVE COMPOUND

MSDS Date:01/01/1989

FSC:8030

NIIN:00-938-1947

MSDS Number: BHYKN

=== Responsible Party ===

Company Name:MALTER INTERNATIONAL

Address:80 FIRST STREET

City:GRETNA

State:LA

ZIP:70053

Country:US

Info Phone Num:504-362-3232 OR 1-800-535-4095

Emergency Phone Num:504-362-3232 OR 1-800-535-4095

CAGE:27978

=== Contractor

Identification ===

Company Name:MALTER INTERNATIONAL BULK CHEMICAL DIVISION

Address:80 FIRST STREET

Box:City:GRETNA

State:LA

ZIP:70053

Country:US

Phone:504-362-3232, OR 800-535-4095

CAGE:27978

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT 140 HI FLASH ALIPHATIC HYDROCARBON BLEND

Fraction by Wt: 12.5%

OSHA PEL:1000 PPM

Ingred Name:INHIBITOR BLEND INCLUDING THE BARIUM SOAP OF AN OXYGENATED  
HYDROCARBON

Fraction by Wt: 12.5%

Ingred Name:SOLVENT FR

EON 113  
Fraction by Wt: 75%  
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:LIGHT HEADEDNESS, GIDDINESS, SHORTNESS  
OF BREATH, POSSIBLE NARCOSIS, POSSIBLE CARDIAC ARRHYTHMIAS AT HIGH  
CONCENTRATIONS.  
Effects of Overexposure:LIGHT HEADEDNESS, GIDDINESS, SHORTNESS OF  
BREATH, POSSIBLE NARCOSIS, POSSIBLE CARDIAC ARRHYTHMIAS AT HIGH  
CONCENTRATIONS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. DO NOT  
GIVE EPINEPHINE OR SIMILAR DRUGS. SKIN AND/OR EYES: FLUSH WITH  
WATER.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:163 F/ 73 C  
Extinguishing Media:MECHANICAL FOAM, DRY CHEMICALS, WATER FOG, CO2.  
Fire Fighting Procedures:STRAIGHT WATER STREAM WOULD SPREAD OIL FIRES.  
Unusual Fire/Explosion Hazard:VAPO  
R ACCUMULATION WOULD FLASH AND/OR  
EXPLODE IF IGNITED.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA-ESPECIALLY LOW PLACES WHERE  
HEAVY VAPORS MIGHT COLLECT. REMOVE FLAMES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS IN A CLEAN, DRY AREA.  
DO NOT HEAT ABOVE 125 F.  
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:USE IARI MASK IN HIGH CONCENTRATIONS.  
Ventilation:USE LOCAL EXHAUST WHEN LARGE AMOUNTS ARE RELEASED.  
Protective Gloves:USE WHEN HANDLING LIQUID.  
Eye Protection:USE WHEN HANDLING LIQUID.  
Other Protective Equipment:NONE.  
Work Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:V2  
Boiling Pt:B.P. Text:117 F-390 F  
Melt/Freeze Pt:M.P/F.P Text:NA  
Vapor Pres:  
334 MMHG  
Vapor Density:6.5(AIR=1)  
Spec Gravity:1.25-1.30 H2O=1  
Evaporation Rate & Reference:0.3  
Solubility in Water:NEGLIGIBLE.  
Appearance and Odor:DARK AMBER WITH ORGANIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ALKALI OR ALKALINE EARTH METALS-POWERED AL, ZN, BE, ETC.  
Stability Condition to Avoid:OPEN FLAMES OR HIGH TEMPERATURE.  
Hazardous Decomposition Products:HYDROCHLORIC AND HYDROFLORIC  
ACIDS-POSSIBLE CARBO  
NYL HALIDES

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM BY DISTILLATION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek comp

etent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.