

CROWN PAINT COMPANY -- BLACK WRINKLE ENAMEL, M105 -- 8010-00-530-8380

=====
Product Identification
=====

Product ID:BLACK WRINKLE ENAMEL, M105

MSDS Date:09/16/1986

FSC:8010

NIIN:00-530-8380

MSDS Number: BJCQH

=== Responsible Party ===

Company Name:CROWN PAINT COMPANY

Address:3400 N.E. 4TH STREET

City:OKLAHOMA CITY

State:OK

ZIP:73117

Info Phone Num:(405) 232-8580

Emergency Phone Num:(405) 232-8580

CAGE:OG5U8

=== Contractor Identification ===

Company Name:CROWN INDUSTRIAL PRODUCTS CO

Address:HWY 47 N

Box:350

City:HEBRON

State:IL

ZIP:60034

Country:US

Phone:815-648-2424

CAGE:92381

Company Name:CROWN PAINT COMPANY

Address:1801 WEST SHERIDAN

City:OKLAHOMA CITY

State:OK

ZIP:73106

Phone:(105) 232-8580

CAGE:OG5U8

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 33.3%

Other REC Limits:STEL 400

PPM
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 17.0%
Other REC Limits:100 PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALCOHOL
Fraction by Wt: 1.0%
ACGIH TLV:400 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
He

alth Hazards Acute and Chronic:SKIN/EYES: PRIMARY IRRITATION.
INHALATION: NERVOUS SYSTEM DEPRESSION, HEADACHE, DIZZINESS,
STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS, COMA. INGESTION:
HARMFUL/FATAL.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN/EYES: PRIMARY IRRITATION. INHALATION:
NERVOUS SYTEM DEPRESSION, HEADACHE, DIZZINESS, STAGGERING GAIT,
CONFUSION, UNCONSCIOUSNESS, COMA. INGESTION: HARMFUL/FATAL.
OVEREXPOSURE HAS BEEN SUGGESTED A S A CAUSE OF THE
FOLLOWING IN
HUMANS: LIVER ABNORMALITIES.

===== First Aid Measures =====

First Aid:EYE/SKIN: FLUSH W/WATER FOR AT LEAST 15 MINS. GET MEDICAL
ATTENTION. INHALATION: REMOVE FROM EXPOSURE RESTORE BREATHING.
INGESTION: DON'T INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:55F
Lower Limits:1.2%
Extinguishing Media:FOAM, CO2
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER S

PRAY MAY BE

USED TO COOL CONTAINERS. USE FOG NOZZLES IF WATER IS USED.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL ON PAPER VERMICULITE FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:EMPTY CONTAINERS MAY BE HAZARDOUS WHEN EMPTIED, GROUND CONTAINERS IN EXPLOSIVE ATMOSPHERE WHEN POURING LIQUID.

Other Precautions:FLAMMABLE LIQUID DON'T USE NEAR SPARKS, HEAT OR OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, WEAR APPROVED SELF CONTAINED BREATHING APPARATUS W/FULL FACE PIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE IS ADVISED.

Ventilation:SUPPLY SUFFICIENT MECHANICAL/LOCAL EXHAUST VENTILATION TO KEEP AIR

Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:51.3%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS

Stability Condition to Avoid:SPARKS, HEAT, FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION OR TOXIC SUBSTANCE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This informa

tion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.