

FIBER MATERIALS, INC. -- FLEXFRAM 605TH -- 8030-00-097-9088

===== Product Identification =====

Product ID:FLEXFRAM 605TH

MSDS Date:08/27/1990

FSC:8030

NIIN:00-097-9088

Kit Part:Y

MSDS Number: BJDMW

=== Responsible Party ===

Company Name:FIBER MATERIALS, INC.

Address:BIDDEFORD INDUSTRIAL PARK

City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Info Phone Num:207-282-5911

Emergency Phone Num:207-282-5911

CAGE:KO060

=== Contractor Identification ===

Company Name:FIBER M

ATERIALS INC

Address:BIDDEFORD INDUSTRIAL PARK

Box:City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Phone:207-282-5911

CAGE:62500

Company Name:FIBER MATERIALS, INC.

Address:5 MORIN ST

Box:City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Phone:207-282-5911

CAGE:KO060

===== Composition/Information on Ingredients =====

Ingred Name:SILICA, AMORPHOUS

Other REC Limits:NONE KNOWN

OSHA PEL:20 MPPCF

ACGIH TLV:5 MPPCF (RESPIRABLE)

Ingred Name:EPOXY RESIN (DIGLYCIDYL ETHER OF BIS PHENOL A)

Oth

er REC Limits:NONE KNOWN

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:REMOVAL OF CURED MATERIAL BY GRINDING MAY RESULT IN SUSPENDING SILICA DUST, CARBON FIBERS, AND NUISANCE DUSTS IN THE AIR. INHALATION OF EPOXY RESINS MAY BE IRRITATING AND SENSITIZERS. HOWEVER, RESIN

IS NOT VOLATILE AND GENERALLY DOES NOT PRESENT SERIOUS HAZARD BY INHALATION.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:PRIMARY IRRITATION OF SKIN ON PROLONGED CONTACT. IRRITATING TO THE EYES.

Medical Cond Aggravated by Exposure:ALLERGIES AND/OR OTHER RESPIRATORY CONDITIONS.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR, GET MD. EYE:FLUSH THOROUGHLY W/WATER 15 MIN. SKIN:WASH W/SOAP AND WATER. I

NGEST:INDUCE VOMITING AND GET MD IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:315F,157C

Extinguishing Media:WATER SPRAY, CO*2, DRY CHEMICAL

Fire Fighting Procedures:FOR LARGE FIRES, USE WATER SPRAY, FOG, OR FOAM. DIKE WATER RUN-OFF. PREVENT ENTRY INTO SEWERS OR NATURAL WATERS. WEAR FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:TOXIC FUMES WILL BE EVOLVED IF UNMIXED MATERIAL IS INVOLVED IN A FIRE. WEAR SCBA.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE. NIOSH APPROVED RESP PROT AND OTHER PROT EQUIP AS NECESSARY TO PREVENT SKIN & EYE CONTACT. IF WARM, PUMP INTO SALVAGE DRUM. SOAK UP RESIDUE & SML SPILLS W/ABSORBENT MAT SUCH AS CLAY & PUT IN TIGH T CONTAINER. IF USE SOLVNT, WATCH FIRE HAZRDS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling

and Storage Precautions:STORE IN TIGHT, STURDY CONTAINERS.
HANDLE I/A/W HAZARD POTENTIAL.
Other Precautions:REMOVE CONTAMINATED CLOTHING & PROTECTIVE GEAR.
DECONTAMINATE. DESTROY LEATHER ARTICLES, INCLUDING SHOES THAT
CANNOT BE DECON. ANSI CLASSIFICATION 2. REMOVAL OF CURED MATERIAL
SHOULD BE ACCOMPLISHED W /NIOH APPROVED RESPIRATORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOH APPROVED RESP W/ORGANIC VAPOR CARTRIDGE.
N
/A WITH LOCAL EXHAUST.
Ventilation:LOCAL:IN MIXING & APPL. AREAS. MECH:RECOMMENDED.
SPECIAL:REMOVAL OF CURED W/NIOH APPROVED DUST RESP.
Protective Gloves:RUBBER GLOVES TO PREVENT SKIN CONTACT.
Eye Protection:GOGGLES OR FACE SHIELD.
Other Protective Equipment:AS NECESSARY TO PREVENT BODY CONTACT.
Work Hygienic Practices:AVOID SMOKING, EATING, AND DRINKING IN THE WORK
AREA.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties ==
=====

Boiling Pt:B.P. Text:600F,316C
Vapor Pres:.01 @ 70F
Vapor Density:9
Spec Gravity:1.503
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GRAY VISCOUS LIQUID, MILD AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, CHLORINATED ORGANIC COMPOUNDS.
Stability Condition to Avoid:RESINS WITH CONSIDERABLE HEAT WITH HOT
RESINS.
Hazardous Decomposition Products:CO*2, AL
DEHYDES, ACIDS, NO*2, SO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W FED, STATE AND LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizi

ng this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.