

PRATT & LAMBERT INC -- LACQUER-C/N GLOSS BROWN 10080 ID 786112 -- 8010-00-257-5376

=====  
Product Identification  
=====

Product ID:LACQUER-C/N GLOSS BROWN 10080 ID 786112

MSDS Date:08/21/1990

FSC:8010

NIIN:00-257-5376

MSDS Number: BJFDG

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-73

3-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25%

Other REC Limits:L

FL 2.0/UFL 11.0  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
Other REC Limits:LFL 3.0/UFL 13.0  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE  
CAS:9004-70-0  
RTECS #:FJ6000000  
Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: 10%  
Other REC Limi  
ts:LFL 1.0/UFL 11.0  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (SARA III)  
CAS:141-78-6  
RTECS #:AH5425000  
Fraction by Wt: < 5%  
Other REC Limits:LFL 2.0/UFL 11.0  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: < 5%  
Other REC Limits:LFL 1.7/UFL 7.1  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DO

T Rpt Qty:1000 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:VM&P NAPHTHA (VP 40 MM HG @ 20C)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 20%

Other REC Limits:LFL 1.0/UFL 6.0

OSHA PEL:300 PPM/400 PPM STEL

ACGIH TLV:300 PPM/1350 MG/CU.M

Ingred Name:VOC 4.95 LB/GAL LESS WATER

& NEGLIGIBLY PHOTOCHEMICALLY

REACTIVE MATERIALS 594 G/L LESS WATER.

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 18.20 LB/GAL SOLIDS 2184 G/L SOLIDS.

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTINAL IRRITATION & CH

EMICAL PNEUMONITIS. INHALATION MAY CAUSE NOSE/THROAT

IRRITATION & ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. EYE & SKIN

IRRITANT; HARMFUL AMOUNTS CAN CAUSE SKIN DEFATTING. OTHER EFFECTS:

LIVER DAMAGE, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE & DEATH.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS

A POTENTIAL CARCINOGEN BY THE NATIONAL TOXICOLGY PROGRAM.

Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, VOMITING,

CONFUSION & SEVERE IRRITATION REACTION

IF PRODUCT IS SWALLOWED,  
INHALED, ABSORBED THROUGH SKIN, OR GETS INTO EYES.  
Medical Cond Aggravated by Exposure:CHEMICAL PNEUMONITIS, ACUTE CENTRAL  
NERVOUS SYSTEM DEPRESSION, LIVER DAMAGE, PERMANENT BRAIN & NERVOUS  
SYSTEM DAMAGE & DEATH.

===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL POISON CONTROL  
CENTER IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY.  
IF BREATHING STOPPED, GIVE CPR & KEEP  
WARM & QUIET. EYE: FLUSH WITH  
LARGE AMOUNTS OF WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS  
CONTINUOUSLY. SKIN: REMOVE CONTAMINATED CLOTHING & WASH AFFECTED  
AREA WITH SOAP & WATER. GET MEDICAL ATTENTION IMMEDIATELY FOR ANY  
OF THESE CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:20F/-7C  
Lower Limits:SEE INGRED.  
Upper Limits:SEE INGRED.  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR  
FLAMMABLE LIQUID FIRES. POLYME  
R FOAM IS PREFERRED FOR LARGE FIRES.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE BUT USED TO COOL  
EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP & POSS AUTO-IGNITE  
EXPLOSION. IF WATER USED, FOG NOZZLES ARE PREFERRED.  
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS  
MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY  
APPARENT. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE  
SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO  
COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARK TOOLS.  
PREVENT CONTAMINATION OF SEWERS, STREAMS & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F.  
STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.  
Other Precautions:EMPTY CONTAINERS SHOULD NOT BE WASHED OR

REUSED FOR

ANY PURPOSE AND SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DISPOSE AS HAZARDOUS WASTE, IGNITABLE, D001.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONF

INED AREAS USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation: DILUTE & LOCAL EXHAUST RECOMMENDED TO CONTROL CONCENTRATION OF HAZARDOUS INGREDIENTS.

Protective Gloves: WEAR SOLVENT IMPERMEABLE GLOVES.

Eye Protection: SAFETY SPECTACLES W/FACE & SIDE SHIELDS.

Work Hygienic Practices: DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE & KEEP AWAY FROM CHILDREN.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 203 TO 302F

Vapor Density: > THAN AIR

Spec Gravity: 1.0

Evaporation Rate & Reference: SLOWER THAN ETHER.

Percent Volatiles by Volume: 72 %

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, HEAT BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

=====  
===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by t

he compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.