

PRATT & LAMBERT INC -- ENAMEL ALKYD GLOSS GREEN 14110 ID 742422 -- 8010-00-286-7727
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS GREEN 14110 ID 742422

MSDS Date:08/23/1990

FSC:8010

NIIN:00-286-7727

MSDS Number: BJFDK

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-

733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (VP 2 MM HG @ 20C)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 45%

Other RE

C Limits:LFL 1.0/UFL 7.0
OSHA PEL:100 PPM/525 MG/CU.M.
ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:LEAD CHROMATE (OSHA-CEIL .1000 MG/CU.M.) (SARA 313
REPORTABLE)

CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:.0500 MG/CU.M.
ACGIH TLV:.0500 MG/CU.M.

Ingred Name:VOC 3.97 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 476 G/L LESS WATER.

RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 10.27 LB/GAL SOLIDS 12
32 G/L SOLIDS.

RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:HYDROQUINONE (SARA III)

CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 39C
Lower Limits:SEE INGRED.
Upper Limits:SEE INGRED.

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:FF SHOULD WEAR SELF-CONTAINED BREATHING APPAR.
WATER MAY BE USED TO COOL EXPOSED CONTAINERS TO PEVENT POSSIBLE
AUTO-IGNITE EX

PLOS. USE FOG NOZZLES WITH WATER.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE
HEALTH HAZ. SYMPTOMS MAY NOT BE IMMED APPARENT. GET MED ATTN. KEEP
CLOSED CONTAINERS AWAY FROM HEAT; COULD EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE
SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO
COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARKING

TOOLS.

PREVENT CONTAMINATION OF S EWER, STREAMS, & GROUNDWATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F.

STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:NEVER WASH OR REUSE EMPTY CONTAINERS FOR ANY PURPOSE.

CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE, CUT OR USE PRESSURE TO EMPTY CONTAINERS. DISPOSE AS HAZARDOUS

WASTE, IGNITABLE D001, EP TOXIC D008.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED CHEM CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONFINED AREAS USE A NIOSH /MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:DILUTE & LOCAL EXHAUST RECOMMENDED TO CONTROL CONCENTRATE OF HAZARDOUS INGREDIENTS.**

Protective G

loves:WEAR SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. WASH HANDS AND FACE THOROUGHLY BEFORE EATING OR DRINKING. PREVENT SKIN CONTACT.

Supplemental Safety and Health

** DECOMPOSITION PRODUCTS THAT ARE GENERATED WHEN WELDNG, CUTTING, OR BRAZING OBJECTS COATED WITH THIS PRODUCT SHOULD BE REMOVED. THIS PRODUCT CONTAINS LEAD, WHICH, IF PRESENT IN WASTE AT 5.0 MG/1 OR MORE AFTER BEING EXTRACTED, IS CONSIDERED EP TOXIC, AND THEREFORE A HAZARDOUS WASTE BEING D008.

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:302 TO 390F

Vapor Density:> THAN AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:61%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOU

RCES OF
IGNITION.

Hazardous Decomposition Products: BURNING, HEAT BY WELDING/CUTTING,
PRODUCES SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF
CHROMIUM AND LEAD.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS.
INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS. OBSERVE PRECAU
TIONS FOR DISP OF FLAMMABLE MATERIALS.
CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional
advice to verify and
assume responsibility for the suitability of this information to their
particular situation.