

SYBRON CHEMICALS INC -- 31006/31054/31034 -- 4610-00-363-5770

===== Product Identification =====

Product ID:31006/31054/31034

MSDS Date:10/21/1985

FSC:4610

NIIN:00-363-5770

MSDS Number: BJFPB

=== Responsible Party ===

Company Name:SYBRON CHEMICALS INC

Address:BIRMINGHAM RD

Box:66

City:BIRMINGHAM

State:NJ

ZIP:08011

Country:US

Info Phone Num:609-893-1100

Emergency Phone Num:609-893-1100

CAGE:76465

=

== Contractor Identification ==

Company Name:BARNSTEAD/THERMOLYNE CORP, DIV OF SYBRON CORP

Address:2555 KERPER BLVD

Box:City:DUBUQUE

State:IA

ZIP:52001-1461

Country:US

Phone:800-446-6060/ FAX: 319-589-0516

CAGE:05852

Company Name:SYBRON CHEMICALS INC,SUB OF SYBRON CORP

Address:BIRMINGHAM RD

Box:66

City:BIRMINGHAM

State:NJ

ZIP:08011

Country:US

Phone:609-893-1100

CAGE:76465

===== Composition/Information on Ingredients =====

Ingred Name:ANION EXCHANGE POLYMER

Fraction by Wt: 44

-56%

Ingred Name:WATER  
Fraction by Wt: 44-56%

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:CAN CAUSE EYE IRRITATION. SKIN:MAY  
CAUSE SKIN IRRITATION.  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.  
Medical Cond Aggravated by  
Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH EYES WITH COPIOUS QUANTITIES OF WATER FOR 15 MIN.  
SEE MD. SKIN:FLUSH WITH WATER.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL, CO\*2 OR WATER FOG.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA  
OR EQUIVALENT.  
Unusual Fire/Explosion Hazard:TOXIC DECOMPOSITION PRODUCTS.

=====

===== Accidental Release Measures =====

Spill Release Procedures:SLIPPERY FLOOR; SWEEP UP SPILLED MATERIAL.  
DISPOSE AS ORDINARY TRASH.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID FREEZING/STORING FOR LONG  
PERIODS ABOVE 100F.AVOID CONTACT W/STRONG OXIDIZING AGENTS I.E.  
NITRIC ACID. MATL SHOULD NOT BE ALLOWED TO DRY OUT.  
Other Precautions:DO NOT PACK

MATERIAL IN UNPROTECTED GLASS COLUMNS.  
STRONG OXIDIZING AGENTS SUCH AS NITRIC ACID CAN CAUSE EXPLOSIVE REACTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NORMAL ROOM.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES.

Other Protective Equipment:LOCAL EYEWASH FACILITY.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURE

R.

Supplemental Safety and Health

THIS IS NOT A KIT. THIS IS PART A OF A THREE PART SINGLE PRODUCT.

===== Physical/Chemical Properties =====

Spec Gravity:1.1

pH:9-11

Evaporation Rate & Reference:1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT SPHERICAL BEADS SLIGHT TRIMETHYLAMINE ODOR.

Percent Volatiles by Volume:55-70%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH S

TRONG OXIDIZING AGENTS, NITRIC ACID.

Stability Condition to Avoid:TEMPERATURES ABOVE 400F.

Hazardous Decomposition Products:CO, CO\*2, STYRENE, N(CH\*3)\*3, AMMONIA, SO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF MATERIAL, ITS RINSINGS OR SPILL RESIDUES MUST BE I/A/W FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements o

f the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.