

PRATT & LAMBERT INC -- LACQUER ACRYLIC GREEN 14187, ID 794430 -- 8010-00-935-7071
===== Product Identification =====

Product ID:LACQUER ACRYLIC GREEN 14187, ID 794430

MSDS Date:09/12/1990

FSC:8010

NIIN:00-935-7071

MSDS Number: BJFQK

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA-CEIL .1000 MG/CU.M.) (SARA 313 REPORTABLE)

CAS:7758-97-6

RTECS #:GB2975000

F

raction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:.0500 MG/CU.M.
ACGIH TLV:.0500 MG/CU.M.

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 20%
Other REC Limits:LFL 1.1
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 20%
Other REC Limits:LFL 2.0/UFL 10.0
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STE
L 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)
CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: < 5%
Other REC Limits:LFL .3
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:LFL 3.0/UFL 13.0
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 10%
Other REC Limits:LFL

1.7/UFL 7.1
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC 5.00 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 600 G/L LESS WATER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 16.56 LB/GAL SOLIDS 1987 G/L SOLIDS
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Repor

ts of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTINAL
IRRITATION & CHEMICAL PNEUMONITIS. MAY SEVERELY IRRITATE NOSE,
THROAT, EYES & SKIN. OTHER EFFECTS: DAMAGE TO BLOOD FORMING,
KIDNEYS, URINE, REPRODUCTIVE SYSTEM, B RAIN, NERVOUS SYSTEM.
DELIBERATELY CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL OR
FATAL.

Explanation of Carcinogenicity:CHROMATES MAY CAUSE LUNG CANCER.

Effects of Overexposure:HEADACHES, D

IZZINESS, NAUSEA, VOMITING,

CONFUSION, LOSS OF APPETITE, METALLIC TASTE IN MOUTH, ANXIETY,
CONSTIPATION, WEAKNESS, INSOMNIA, MUSCLE & JOINT PAIN, FINE
TREMORS, NUMBNESS, HYPERACTIVITY, COL IC, & SEVERE IRRITATION
REACTION IF PRODUCT IS SWALLOWED, INHALED, ABSORBED THROUGH SKIN,
OR GETS INTO EYES.

Medical Cond Aggravated by Exposure:REPORTS HAVE ASSOCIATED PROLONGED
AND REPEATED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE. PREEXISTING KIDNEY
CONDITIONS MAY BE
AGGRAVATED BY EXPOSURES TO LEAD.

===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL POISON CONTROL
CENTER IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY. IF
BREATHING STOPPED, GIVE CPR & KEEP WARM. EYE: FLUSH WITH LARGE
AMOUNTS OF WA TER FOR 15 MINUTES LIFTING UPPER/LOWER LIDS
CONTINUOUSLY. SKIN: REMOVE CONTAMINATED CLOTHING AND WASH AFFECTED
AREA WITH SOAP & WATER. GET MED

ICAL ATTENTION IMMEDIATELY FOR ANY
OF THESE CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:24F/-4C

Lower Limits:SEE INGRED

Upper Limits:SEE INGRED

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR
FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER BY BE INEFFECTIVE BUT USED TO COOL
EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP & POSSIBLE
AUTO-IGNITE EXPLOSION. IF WATER
USED, FOG NOZZLES PREFERRED.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY
APPARENT. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE
SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO
COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARKING TOOLS.
PREVENT CONTAMIN
ATION OF S E WERS, STREAMS, & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F.
STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:NEVER WASH OR REUSE EMPTY CONTAINERS FOR ANY PURPOSE.
CONTAINERS SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER. DO
NOT WELD, BRAZE, CUT OR USE PRESSURE TO EMPTY CONTAINERS. DISPOSE
AS HAZARDOUS W ASTE, IGNITABLE D001, EP
TOXIC D008.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION
MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED CHEM
CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN CONFINED
AREAS USE A NIOSH /MSHA APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:DILUTE & LOCAL EXHAUST RECOMMENDED TO CONTROL CONCENTRATE
OF HAZARDOUS INGREDIENTS.**

Protective Gloves:WEAR SOLVENT IMPERMEA

BLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. PREVENT CONTACT WITH SKIN. WASH HANDS & FACE THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

** REMOVE DECOMPOSITION PRODUCTS THAT ARE GENERATED WHEN WELDING, CUTTING, OR BRAZING OBJECTS COATED WITH THIS PRODUCT. THIS PRODUCT CONTAINS LEAD, WHICH IF PRESENT IN WASTE AT 5.0 MG/L OR MORE AFTER BEING EXTRACTED, IS CONSIDERED EP TOXIC& A HAZARDOUS WASTE UNDER R

CRA REGULATIONS. HAZARDOUS WASTE NO. WOULD BE D008.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 312F

Vapor Density:> THAN AIR

Spec Gravity:1.1

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF

IGNITION.

Hazardous Decomposition Products:BURNING, HEAT BY WELDING/CUTTING, PRODUCES SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, OXIDES CHROMIUM, & LEAD.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS.

INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISP OF FLAMMABLE MATERIALS.

CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.