

FLUORO-PLASTICS INC -- ADHESIVE 85 RESIN -- 8040-01-130-6004

===== Product Identification =====

Product ID:ADHESIVE 85 RESIN

MSDS Date:11/02/1987

FSC:8040

NIIN:01-130-6004

Kit Part:Y

MSDS Number: BJFRV

=== Responsible Party ===

Company Name:FLUORO-PLASTICS INC

Address:G AND VENANGO STS

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Info Phone Num:215-425-5500

Emergency Phone Num:215-425-5500

CAGE:07658

=== Contractor Identification ===

Company Name:FLUORO-PLA

STICS INC

Address:G AND VENANGO STS

Box:City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

CAGE:07658

===== Composition/Information on Ingredients =====

Ingred Name:EPICHLOROHYDRIN & BISPHENOL A

CAS:25036-25-3

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN & EYES

: MILD IRRITATION.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:IRRITATION, SENSITIZATION & DERMATITIS.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH WATER.

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:465F,241C

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY.

Fire Fighting Pro

cedures:USE NIOSH/MSHA APPROVED SCBA AND FULL

PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:DECOMPOSITION & COMBUSTION PRODUCTS MAY
BE TOXIC.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP IN ABSORBENT MATERIAL OR SCRAPE UP.
RESIDUAL CAN BE REMOVED WITH NON FLAMMABLE SOLVENT SUCH AS
METHYLENE CHLORIDE (MFR). RECOMMEND METHYLENE CHLORIDE NOT BE USED
FOR THIS PURPOSE .

Neutralizing Agent:SEE ABOVE

=====

===== Handling and Storage =====

Handling and Storage Precautions:PRACTICE GOOD CAUTION AND PERSONAL
CLEANLINESS TO AVOID SKIN & EYE CONTACT. STORE IN COOL DRY AREA IN
CLOSED CONTAINERS.

Other Precautions:AVOID BREATHING VAPORS OF HEATED MATERIAL. PROMPTLY
REMOVE WET CONTAMINATED NON-IMPERVIOUS CLOTHING, DESTROY
CONTAMINATED LEATHER & ABSORBENT SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CHEMICAL C

ARTRIDGE RESPIRATOR, IF
NEEDED.
Ventilation:LOCAL EXHAUST, MECHANICAL
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:WEAR APPROPRIATE EQUIPMENT TO PREVENT
SKIN/EYE CONTACT. USE OF BARRIER CREAM RECOMMENDED.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Spec Gravity:1.16
Solubility in Water:NONE
Appearance and Odor:WHITE TO YELLOW LIQUID TO SEMI-SOLID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:EXCESSIVE HEATING OVER LONG PERIODS OF
TIME DEGRADES THE RESIN. FIRE CONDITIONS INCREASE VISCOSITY & EEW.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
ALDEHYDES.
Conditions to Avoid Polymerization:WITH ALIPHATIC AMINES IN MASSES
GREAT
ER THAN 1 POUND.

===== Disposal Considerations =====

Waste Disposal Methods:BURN IN ADEQUATE INCINERATOR OR BURY IN AN
APPROVED LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any pe

Person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.