

THE FLAMEMASTER CORPORATION -- E-340, PART B -- 8010-00-164-4389

===== Product Identification =====

Product ID:E-340, PART B

MSDS Date:11/01/1990

FSC:8010

NIIN:00-164-4389

Kit Part:Y

MSDS Number: BJJDG

=== Responsible Party ===

Company Name:THE FLAMEMASTER CORPORATION

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Info Phone Num:818-982-1650

Emergency Phone Num:818-84

8-9560;800-424-9300(CHEMTREC

Preparer's Name:HERBERT H MOORE

CAGE:6N186

=== Contractor Identification ===

Company Name:FIBER MATERIALS INC

Address:BIDDEFORD INDUSTRIAL PARK

Box:City:BIDDEFORD

State:ME

ZIP:04005

Country:US

Phone:207-282-5911

CAGE:62500

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

Company Name:THE FLAMEMASTER CORPORATION

CAGE:6N186

===== Composition/Informati

on on Ingredients =====

Ingred Name:2,4,6-TRI(DIMETHYL AMINO METHYL) PHENOL
CAS:90-72-2
RTECS #:SN3500000
Fraction by Wt: 5%
Other REC Limits:5 PPM (SKIN)

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:VAPOR/MIST CAN IRRITATE THE NOSE AND THROAT. SEVERELY IRRITATING TO EYES AND SKIN. MATERIAL CAN CAUSE SKIN SENSITIZATION AND DERMATITIS. MFR ALSO IDENTIFIES SKIN AND INGESTION AS ROUTES OF ENTRY (FP N).
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HEADACHE, DIZZINESS, TEARING OF EYES AND NOSE IRRITATION. ITCHING OF SKIN WITH SIGN OF REDNESS.
Medical Cond Aggravated by Exposure:ASTHMA. LIVER DISORDERS.

===== First Aid Measures =====

First Aid:EYE AND SKIN CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MD. WASH SKIN WITH SOAP AND WATER. INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O2/ARTIFICIAL RESPIRATION), GET MD (FP N). INGEST: GET MD IMMEDIATELY .

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>200F;93C
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER SPRAY
Fire Fighting Procedures:IN CONFINED AREAS WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:OXIDES OF NITROGEN, MAY BE PRODUCTS OF COMBUSTION

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AND RETURN TO CONTAINER. WASH AREA WITH SOAP AND WATER.
Neutralizing Agent:ACID

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREAS AWAY FROM DIRECT SUNLIGHT. KEEP IN CLOSED CONTAINERS.
Other Precautions:AVOID CONTACT WITH SKIN, EYES AND

CLOTHING. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC
VAPOR CANISTER
Ventilation:LOCAL EXHAUST: YES. MECHANICAL (GENERAL): FAN.
Protective Gloves:RUBBER
Eye Protection:CHEMICAL WORKERS GOGGLES
Other Protective Equipment:APRON AND SAFETY SHOES
Work Hygienic Practices:DO NOT SMOKE, DRINK OR EAT IN WORK AREAS
Supplemental Safety and Health
NONE SPECIFIED BY
MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:B3
Boiling Pt:B.P. Text:550F,288C
Melt/Freeze Pt:M.P/F.P Text:LIQ@RM TEMP
Vapor Pres: