

BONDED PRODUCTS INC -- MILR19907C LIQUID RESIN PART A / BOATKITLR -- 2090-00-372-6064
===== Product Identification =====

Product ID:MILR19907C LIQUID RESIN PART A / BOATKITLR

MSDS Date:05/18/1989

FSC:2090

NIIN:00-372-6064

Kit Part:Y

MSDS Number: BJKNJ

=== Responsible Party ===

Company Name:BONDED PRODUCTS INC

Address:439 S BOLMAR ST

Box:39

City:WEST CHESTER

State:PA

ZIP:19381-0039

Country:US

Info

Phone Num:215-696-9220

Emergency Phone Num:215-696-9220

Preparer's Name:A NICHOLAS ROSA

CAGE:19092

=== Contractor Identification ===

Company Name:ABBEY COLOR INC DBA ABBEY PRODUCTS AND BONDED

Address:400 E TIOGA ST

Box:City:PHILADELPHIA

State:PA

ZIP:19134-1127

Country:US

Phone:215-739-9960

CAGE:19092

Company Name:CAN-TITE RUBBER CORP

Address:33 REDFERN AVE

Box:City:INWOOD LONG ISLAND

State:NY

ZIP:11696-3401

Country:US

CAGE:16486

Company Name:HARVEY-WESTBURY CORP

Address:75 URBAN AVE

City:WESTBUR

Y
State:NY
ZIP:11590
Country:US
Phone:516-334-7770
CAGE:56237

=====
===== Composition/Information on Ingredients =====

Ingred Name:EPON 820, EPOXIDE ORAL RAT, LD50: 11400 MG/MK
CAS:25068-38-6
RTECS #:SL6475000

Ingred Name:REACTIVE EPOXY DILUENT

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 M
G/M3 TDUST; 9192

Ingred Name:SILICON DIOXIDE, AMORPHOUS ORAL RAT, LD50: 3160 MG/KG
CAS:112945-52-5
RTECS #:VV7310000
OSHA PEL:20 MPPCF
ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

LD50 LC50 Mixture:SEE INGREDIENTS
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CAN RESULT IN SKIN IRRITATION
AFTER REPEATED OR PROLONGED EXPOSURE. CHRONIC: NO INFORMATIO

N

FOUND.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:PROLONGED OR REPEATED EXPOSURE CAN CAUSE HEADACHE, RESPIRATORY IRRITATION, IRRITATION TO SKIN/EYES. CAN PRODUCE A SKIN RASH, IRRITATION AND REDNESS OF SKIN. CAN CAUSE ALIMENTARY TRACT AND STOMACH DISCOMFORT IF INGESTED.

Medical Conditions Aggravated by Exposure:ALLERGIES, SKIN ABRASIONS, HEAD COLDS AND EXISTING SKIN ABNORMALITIES.

=====
===== First Aid Measures =====

First

First Aid:INHAL: REMOVE VICTIM TO FRESH AIR, GIVE OXYGEN, APPLY CPR IF REQUIRED. GET MEDICAL HELP. SKIN: WASH THOROUGHLY WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. INGESTION: IF PATIENT IS CONSCIOUS, GIVE LARGE QUANTITIES OF WATER, GET MEDICAL HELP.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>250F,>121C

Extinguishing Media:

FOAM, CO₂, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS. REMAIN UPWIND FROM FIRE. SPRAY WATER ON CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:HANDLE PRODUCT AS A COMBUSTIBLE MATERIAL WHEN EXPOSED TO BURNING OR FIRE. CONTAINERS EXPOSED TO FIRE CAN DEVELOP PRESSURE AND BURST.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. REMOVE SOURCES OF IGNITION.

WEAR APPROVED RESPIRATORY EQUIPMENT & NECESSARY EQUIPMENT TO PROTECT SKIN & EYE CONTACT. SHOVEL OR SCRAP INTO METAL CONTAINERS. SOAK UP RESIDUE WITH ABSORBENT MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:WORK IN A WELL VENTILATED AREA. PREVENT CONTACT WITH SKIN, EYES & CLOTHING. AVOID BREATHING VAPORS. USE PROTECTIVE EQUIP. STORE IN A WELL V

ENTILATED AREA TH

Other Precautions:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. DESTROY CONTAMINATED SHOES AND OTHER LEATHER ARTICLES IF HEAVILY CONTAMINIATED. USE RUBBER GARMENTS. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATORY EQUIPMENT AS REQUIRED TO PREVENT VAPOR EXPOSURE.

Ventilation:ADEQUATE VENTILATION TO CONTROL VAPOR EXPOSURE AWAY FROM OPERAT

OR.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL SPLASH PROOF GOGGLES

Other Protective Equipment:IMPERVIOUS PROTECTIVE GARMENTS TO PREVENT BODY CONTACT. SAFETY SPRAY OR SHOWER AND EYE BATH.

Work Hygienic Practices:PRACTICE GOOD PERSONAL HYGIENE. WASH EXPOSED SKIN AREAS AFTER HANDLING PRODUCT, ESPECIALLY BEFORE EATING.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>2

50F,>121C

Spec Gravity:1.1-1.2

Solubility in Water:VERY SLIGHT

Appearance and Odor:WHITE COLORED LIQUID WITH A CHARACTERISTIC ODOR

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING AGENTS AND MINERAL ACIDS.

Stability Condition to Avoid:OXIDIZING AGENTS AND ACIDS. HIGH TEMPERATURES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND SMOKE.

=====
===== Disposal Considerations =====

=====

Waste Disposal Methods: REACT THIS PART C WITH PART D AND DISPOSE I/A/W
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent p
rofessional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.