

PRATT AND LAMBERT INC -- LACQUER ACRYLIC BLACK 37038, ID 794704 -- 8010-00-830-1822
===== Product Identification =====

Product ID:LACQUER ACRYLIC BLACK 37038, ID 794704

MSDS Date:09/12/1990

FSC:8010

NIIN:00-830-1822

MSDS Number: BJKLB

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:LFL 1.1

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Na

me:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 20%

Other REC Limits:LFL 2.0/UFL 10.0

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000

Fraction by Wt: < 5%

Other REC Limits:LFL 0.3

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 5%

Other R

EC Limits:LFL 3.0/UFL 13.0

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

Other REC Limits:LFL 1.7/UFL 7.1

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTA

LLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: < 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred
Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: < 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:VOC 4.95 LB/GAL LESS WATER & NEGLIGIBLY PHOTOCHEMICALLY
REACTIVE MATERIALS 594 G/L LESS WATER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 16.04 LB/GAL SOLIDS 1925 G/L SOLIDS
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING MAY CAUSE GASTROINTESTINAL IRRITATION & CHEMICAL PNEUMONITIS. INHALATION MAY CAUSE NOSE/THROAT IRRITATION & ACUTE CENTRAL NERVOUS SYS DEPRESSION. EYE & SKIN IRRITANT; HARMFUL AMTS CAN BE AB SORBED THROUGH SKIN & CAUSE DEFATTING. OTHER EFFECTS: LIVER DAMAGE, RESPIRATORY CONDITIONS, AND LUNG DISEASE.

Explanation of

Carcinogenicity:CRYSTALLINE SILICA MAY CAUSE LUNG DISEASE & HAS BEEN LISTED AS A CARCINOGEN BY THE IARC.

Effects of Overexposure:HEADACHES, DIZZINESS, NAUSEA, VOMITING, CONFUSION & SEVERE IRRITATION REACTION IF PRODUCT IS SWALLOWED, INHALED, ABSORBED THROUGH SKIN, OR GETS INTO EYES.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA. REPORTS ASSOCIATED PROLONGED & REPEATED OCCUPATIONAL OVEREXPOSURE TO

SOLVENTS W/PERM BRAIN & NERVOUS SYS DAMAGE.

===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY. IF BREATHING STOPPED, GIVE CPR & KEEP WARM & QUIET. EYE: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS CONTINUOUSLY. SKIN: REMOVE CONTAMINATED CLOTHING & WASH AFFECTED AREA WITH SOAP & WATER. GET MEDICAL ATTENTION IMMEDIATELY FOR ANY OF THESE CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:24F/-4C

Lower Limits:SEE INGRED

Upper Limits:SEE INGRED

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL FOR FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILDUP & POSSIBLE AUTO-IGNITE/EXPLOSION. USE FOG N

OZZLES WITH WATER.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS
MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY
APPARENT. OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE
SOURCES, CONTAIN SPILL WITH INERT MATERIAL, TRANSFER LIQUID TO
COVERED METAL CONTAINERS FOR DISPOSAL. USE ONLY NON-SPARK TOOLS.
PREVENT CONTAMINATION OF SEWE
RS, STREAMS & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F.
STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:EMPTY CONTAINERS SHOULD NOT BE WASHED OR REUSED FOR
ANY PURPOSE AND SHOULD BE GROUNDED & BONDED TO RECEIVING CONTAINER.
DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO
EMPTY. DISPOSE AS HAZARDOUS WASTE, IGNITABLE, D001.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN WELL VENTILATED AREAS, RESPIRATORY PROTECTION
MAY NOT BE REQUIRED. IN RESTRICTED AREAS USE A NIOSH APPROVED
CHEMICAL CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECH PREFILTER. IN
CONFINED AREAS USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.
Ventilation:DILUTE & LOCAL EXHAUST RECOMMENDED TO CONTROL CONCENTRATION
OF HAZARDOUS INGREDIENTS.
Protective Gloves:WEAR SOLVENT IMPERMEABLE GLOVES.
Eye
Protection:WEAR SAFETY SPECTACLES.
Work Hygienic Practices:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER
EACH USE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:175 TO 314F
Vapor Density:> THAN AIR
Spec Gravity:1.1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ST

STRONG ACIDS OR ALKALINE MATERIALS

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING, HEAT BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN I/A/W FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARD WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.