

GENERAL ELECTRIC CO SILICONE PRODUCT DIV. -- G662 SILICONE GREASE COMPOUND --  
6850-00-975-0712

===== Product Identification =====

Product ID:G662 SILICONE GREASE COMPOUND

MSDS Date:03/22/1988

FSC:6850

NIIN:00-975-0712

MSDS Number: BJMGL

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Nam

e:D. A. POLSINELLI

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:GREASE, SILICONE MIXTURE

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS UN

KNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: MILD IRRITATION. INGESTION:

IRRITATION. DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER  
AND GET MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN  
UNCONSCIOUS PERSON. IF CONTACT WITH SKIN, WASH WITH SOAP AND  
WATER.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS  
LISTED BY IARC, NTP, OR OSH

A AS A CARCINOGEN.

Effects of Overexposure:IRRITATION OF EYES AND SKIN.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. RESTORE BREATHING.  
TREAT SYMPTOMATICALLY. GET MEDICAL HELP. EYES: FLUSH IMMEDIATELY  
WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL  
TREATMENT. SK IN: WASH AFFECTED SKIN AREAS WITH SOAP AND WATER.  
REMOVE CONTA  
MINATED CLOTHING. CONSULT A PHYSICIAN IF IRRITATION  
PERSISTS. INGESTION: DO NOT INDUCE VOMITING: GIVE WATER AND GET  
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>500F,>260C  
Autoignition Temp:Autoignition Temp Text:UNKNON  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL  
PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL  
AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH  
DETERGENT AND WATER TO REDUCE SLIPPAGE.  
Neutralizing Agent:N  
ONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.  
Other Precautions:AVOID CONTACT WITH EYES. CONTROL DUST LEVELS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS FOR ORGANIC  
VAPORS. USE NIOSH/MSHA APPROVED AIRLINE TYPE RESPIRATORS OR HOODS  
IN CONFINED AREAS.  
Ventilation:SUFFICIENT VENTILATION

TO CONTROL DUST LEVELS.

Protective Gloves:CLOTH GLOVES

Eye Protection:CHEMICAL SAFETY GLASSES.

Other Protective Equipment:USE DISPOSABLE OR IMPERVIOUS CLOTHING IF  
WORK CLOTHING CONTAMINATION IS LIKELY. USE PROTECTIVE SKIN CREAM IF  
REQUIRED.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING OR USING  
THE WASH ROOM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

THIS MATERIAL IS LISTED AS PART B UNDER THIS NSN. THE PROPERTIES ARE  
DIFFERENT FROM

PART A UNDER THIS SAME NSN.

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:NEGLIGIBLE

Spec Gravity:1.01

Evaporation Rate & Reference: