

PRODUCT RESEARCH & CHEMICAL CORP -- PR-944-F, PART B -- 8010-01-224-4902

===== Product Identification =====

Product ID:PR-944-F, PART B

MSDS Date:02/22/1989

FSC:8010

NIIN:01-224-4902

Kit Part:Y

MSDS Number: BJMKL

=== Responsible Party ===

Company Name:PRODUCT RESEARCH & CHEMICAL CORP

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635

CAGE:DO551

=== Contractor Identifi

cation ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCT RESEARCH & CHEMICAL CORP.

Address:5430 SAN FERNANDO RD./P.O. BOX 1800

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:800-228-5635

CAGE:DO551

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

F

raction by Wt: 5%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:1-METHOXY 2-PROPANOL ACETATE (PMGE ACETATE)
CAS:108-65-6
RTECS #:AI8295000
Fraction by Wt: 93C
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER FOG
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED AIR-SUPPLIED
RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURES MAY CAUSE PRESSURE
BUILDUP IN CLOSED CONTAINERS.

===== Accidental Release
Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WEAR NIOSH/MSHA
APPROVED AIR-SUPPLIED RESPIRATOR FOR MAJOR UNVENTILATED SPILL.
COVER WITH ABSORBENT. SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH
1,1,1-TRICHLOROETHANE.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NONE SPECIFIED BY MANUFACTURER

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN APPLYING IN CONFINED AREAS, OR IN OTHER
CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVELS OF SOLVENT IN
EXCESS OF PEL, USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE
RESPIRATOR OR AIR-SUPPLIED RES PIRATOR.
Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.
Protective Gloves:SOLVENT-RESISTANT GLOVES
Eye Protection:CHEMICAL WORKERS GOGGLES
Other Protective Equipment:NONE SPECI
FIED BY MANUFACTURER
Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING,
SMOKING, OR USING SANITARY FACILITIES .
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER

===== Physical/Chemical Properties =====

Spec Gravity:1.30
Solubility in Water:NEGLIGIBLE
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN
Stability

Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. EPA WASTE NO. D-001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.