

INTEX CHEMICAL INC -- PAINT REMOVER 8570 -- 8010-00-815-2970

===== Product Identification =====

Product ID:PAINT REMOVER 8570

MSDS Date:06/20/1990

FSC:8010

NIIN:00-815-2970

MSDS Number: BJNXG

=== Responsible Party ===

Company Name:INTEX CHEMICAL INC

Box:6648

City:GREENVILLE

State:SC

ZIP:29606

Country:US

Emergency Phone Num:800-424-9300

CAGE:78304

=== Contractor Identification ===

Company Name:INTE

X CHEMICAL INC

Address:122 EDINBURG CT

Box:6648

City:GREENVILLE

State:SC

ZIP:29606-6648

Country:US

Phone:803-879-7100 OR 803-297-4246

CAGE:78304

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIA (SARA III)

CAS:7664-41-7

RTECS #:BO0875000

Fraction by Wt: 5-8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM

ACGIH TLV:25 PPM/35 STEL; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fractio

n by Wt: 47-52%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 15-20%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:SODIUM CHROMATE (SARA III)
CAS:7775-11-3
RTECS #:GB2955000
Fraction by Wt: .1-1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.1 PPM CRO3;CEILING
ACGIH TLV:0.0
5 MG CR/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:MAY COMBINE WITH BLOOD TO FORM
CARBOXYHEMOGLOBIN AS CARBON MONOXIDE DOES.
Explanation of Carcinogenicity:METHYLENE CHLORIDE
Effects of Overexposure:IRRITATED SKIN AND EYES, DIZZINESS, INTESTINAL
DISTRESS. MAY CAUSE KID
NEY AND LIVER DAMAGE.

===== First Aid Measures =====

First Aid:EYE AND SKIN: FLUSH EYES WITH LARGE AMOUNTS OF WATER, HOLDING
LIDS APART. WASH SKIN WITH SOAP AND WATER. INHALATION: REMOVE TO
FRESH AIR. ADMINISTER OXYGEN IF NECESSARY. INGESTION: DO NOT INDUCE
VOMIT ING. GIVE LARGE AMOUNTS OF WATER OR MILK IF AVAILABLE. IF
VOMITING SHOULD OCCUR, KEEP AIRWAYS CLEAR. GET IMMEDIATE MEDICAL
ATTENTION FOR ANY OF THE ABOVE LISTED CONDITIONS.

==

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER, FOG, CARBON DIOXIDE, OR FOAM.

Fire Fighting Procedures:EXTINGUISHING METHOD FOR FIRE SOURCE.

Unusual Fire/Explosion Hazard:NONE.

=====
Accidental Release Measures
=====

Spill Release Procedures:COLLECT SPILL WITH ABSORBENT MATERIAL, DRUM FOR LANDFILL. FLUSH RESIDUE WITH WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:

STORE AWAY FOR INCOMPATIBLE MATERIALS.

STORE IN COOL, DRY PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:MOVE WITH BUNGS IN PLACE. WEAR EYE PROTECTION AND GLOVES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED SELF-CONTAINED.

Ventilation:LOCAL 1

Spec Gravity:1.05-1.06

pH:12 TO*

Viscosity:900-1300 CPS

Solubility in Water:INSOLUBLE

Appearance and Odor:VISCOUS YELLOW LIQUID/ AMMONIA ODOR. *12.4 Percent

Volatiles by Volume:75-85

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

ACIDS.

Hazardous Decomposition Products:EVOLUTION OF NITROGEN, CARBONS.

Conditions to Avoid Polymerization:ACIDS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN APPROPRIATE LANDFILL OR INCINERATE, IN ACCORDANCE WITH PROPER AUTHORITIES.

Disclaimer (provided with this information by the compiler)

g agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.