

THE W.W. HENRY COMPANY -- HENRY FIRETARD FLOOR TILE ADHESIVE 702 -- 8040-00-582-4596

===== Product Identification =====

Product ID:HENRY FIRETARD FLOOR TILE ADHESIVE 702

MSDS Date:02/01/1988

FSC:8040

NIIN:00-582-4596

MSDS Number: BJQDH

=== Responsible Party ===

Company Name:THE W.W. HENRY COMPANY

Address:5608 SOTO STREET

City:HUNTINGTON PARK

State:CA

ZIP:90255

Country:US

Info Phone Num:213-583-4961

Emergency Phone Num:213-583-4961

CAGE:EO968

=== Contractor Ide

ntification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:THE W.W. HENRY CO/HUNTINGTON PARK, CA 90255

CAGE:EO968

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENTS

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

=====

First Aid Measures =====

First Aid:IN CASE OF EYE CONTACT, FLUSH EYES WITH WATER FOR FIFTEEN MINUTES.

===== Fire Fighting Measures =====

Flash Point:> 200F/> 93C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP MATERIAL INTO D.O.T. APPROVED CONTAINER. REMOVE TO SAFE PLACE WHERE MATERIAL CAN DRY.

===== Handlin
g and Storage =====

Handling and Storage Precautions:AVOID EXTREME HEAT OR COLD.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. USE ONLY AS DIRECTED ON LABEL. CLOSE CONTAINER AFTER EACH USE. DO NOT REUSE CONTAINER. AVOID SKIN AND EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Ventilation:USE ADEQUATE VENT.OPEN DOORS/WINDOWS & OTHER MEANS OF FRESH AIR ENTRY & EXHAUST.A SLIGHT ODOR OF ASPHALT/LATEX UNTIL DRY
Protective Gloves:NON
E REQUIRED
Eye Protection:GLASSES TO AVOID SPLASHES.
Other Protective Equipment:NONE REQUIRED
Work Hygienic Practices:WASH SKIN WITH SOAP AND WATER OR HAND CLEANER.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212 TO 250F
Vapor Density:> THAN AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:35-45

===== Stability and Reactivity Data =====

Stability Ind

icator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL DISPOSAL REGULATIONS. DO NOT FLUSH ADHESIVE DOWN DRAIN.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and
d
isclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.