

FENWAL INC. -- TRU-BOND 214, PART B -- 8040-00-800-1811

===== Product Identification =====

Product ID:TRU-BOND 214, PART B

MSDS Date:11/01/1988

FSC:8040

NIIN:00-800-1811

Kit Part:Y

MSDS Number: BJQFQ

=== Responsible Party ===

Company Name:FENWAL INC.

Address:400 MAIN ST.

City:ASHLAND

State:MA

ZIP:01721

Country:US

Info Phone Num:508-881-2000

Emergency Phone Num:508-881-2000

CAGE:0KDPZ

=== Contractor Identification ===

Company Name:FENWAL INC.

Address:400 MAIN S

T

City:ASHLAND

State:MA

ZIP:01721

Country:US

Phone:617-881-2000

CAGE:0KDPZ

Company Name:KIDDE FENWAL INC

Address:400 MAIN ST

Box:City:ASHLAND

State:MA

ZIP:01721-2150

Country:US

Phone:508-881-2000

CAGE:0KDP7

===== Composition/Information on Ingredients =====

Ingred Name:PHENOL

CAS:108-95-2

RTECS #:SJ3325000

Fraction by Wt: < 2%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:5 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE12250

00
Fraction by Wt: < 30%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 PPM
ACGIH TLV:S, 1 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:REPEATED CONTACT CAN CAUSE MILD SKIN
IRRITATION. MILDLY IRRITATING TO EYES. THIS MATERIAL IS A D.O.T
CORROSIVE AND MAY CAUSE BURNS TO SKIN AND EYES. VAPORS MAY CAUSE
IRRITATION TO MUCOUS MEMBRANES OF RESPIRATORY TRACT.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. INHALATION:REMOVE TO FRESH
AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. SKIN:WASH WITH SOAP
& WATER. GET MEDICAL HELP IF IRRITATION PERSISTS. EYES: FLUSH WITH
WATE R FOR 15 MIN. GET MEDICAL HELP IF IRRITATION PERSISTS.
INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR WATER IF CONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Fla
sh Point:168F/76C
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:TOXIC FUMES ARE EVOLVED WHEN THIS
MATERIAL IS IN A FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS AND REMOVE. RESIDUAL CAN BE
REMOVED WITH NON-FLAMMABLE SOLVENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.
Ventilation:LOCAL AND MECHANICAL EXHAUST.
Protective Gloves:IMPERVIOUS GLOVES
Eye Protection:SPLASH-PROOF GOGGLES
Other Protective Equipment:SAFETY SHOWER AND EYE WASH FACILITIES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:> 1
Spec Gravity:1.09
Evaporation Rate & Reference:< 1 (ETHER = 1)
Appearance and Odor:LIGHT AMBER LIQUID, MILD CHARACTERISTIC ODOR

===== Stabil
ity and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS, EPOXY RESINS UNDER UNCONTROLLED
CONDITIONS.
Stability Condition to Avoid:STORAGE AT ELEVATED TEMPERATURES OVER LONG
PERIODS OF TIME.
Hazardous Decomposition Products:CO, CO2, NOX

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH LOCAL POLLUTION
REGULATIONS AND ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.