LOCTITE CORPORATION -- QUICK SET 404 INDUSTRIAL ADHESIVE SPLICING

\_\_\_\_\_

MSDS Safety Information

\_\_\_\_\_\_

FSC: 4940

NIIN: 01-131-1915 MSDS Date: 01/28/1991 MSDS Num: BJQJG

Product ID: QUICK SET 404 INDUSTRIAL ADHESIVE SPLICING

MFN: 03 Kit Part: Y

Responsible Party Cage: 05972

Name: LOCTITE CORPORATION

Address: 1001 TROUT BROOK CROSSING

City: ROCKY HILL (FORMALLY IN NEWINGTON) CT 06067

1

nfo Phone Number: 860-571-5100/FAX 860-571-5465

Emergency Phone Number: 860-571-5100/FAX 860-571-5465

Preparer's Name: STEPHEN REPETTO

Published: Y

\_\_\_\_\_

Contractor Summary

\_\_\_\_\_

Cage: 05972

Name: LOCTITE CORPORATION

Address: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT 06067-3910

Phone: 860-571-5100

Cage: 97403 Name: US ARMY

Address: RESEARCH AND DEVELOPMENT CENTER

City: FORT BELVOIR VA 22060-5

606

Phone: UNKNOWN

\_\_\_\_\_\_

Item Description Information

\_\_\_\_\_

Item Manager: S9C

Item Name: SPLICING KIT O RING

Specification Number: NONE Type/Grade/Class: NONE

Unit of Issue: KT UI Container Qty: 1

Type of Container: UNKNOWN

\_\_\_\_\_

Ingredients

\_\_\_\_\_\_

Cas: 7085-85-0

Name: ETHYL CYANOACRYLATE (CAS NUMB

ER PER MANUFACTURER)

% Wt: 90-95 %

Other REC Limits: NONE SPECIFIED OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 9011-14-7

Name: METHACRYLATE POLYMER (CAS NUMBER PER MANUFACTURER)

% Wt: 5-10 %

Other REC Limits: NONE SPECIFIED OSHA PEL: NOT ESTABLISHED ACGIH TLV: NOT ESTABLISHED

-----

Cas: 123-31-9

RTECS #: MX3500000

Name: HYDROQUINONE (SARA III)

% Wt: 0.1-1 %

Other REC Limits: NONE SPECIFIED

OSHA PEL: 2 MG/M3 ACGIH TLV: 2 MG/M

3; 9192

EPA Rpt Qty: 1 LB DOT Rpt Qty: 1 LB

\_\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_

LD50 LC50 Mixture: > 5000MG/KG LD50 ORAL ESTIMATED

Route Of Entry Inds - Inhalation: NO

Skin: YES Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: BONDS SKIN RAPIDLY AND STRONGLY. SKIN/EYE IRRITANT. Explanation Of Carcinogenicity: PRODUCT CONTAINS NO MATERIALS CURRENTLY

**CLASSIFIED A** 

S CARCINOGENIC BY NTP, IARC OR OSHA.

Signs And Symptions Of Overexposure: VAPOR IS IRRITATING TO EYES AND MUCOUS MEMBRANES ABOVE TLV. PROLONGED AND REPEATED CONTACT TO VAPORS MAY PROVIDE ALLERGIC REACTIONS WITH ASTHMA-LIKE SYMPTOMS IN SENSITIVE INDIVIDUALS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: SKIN: IMMERSE THE BONDED SURFACES IN WARM SOAPY WATER. PEEL OR ROOL THE SURFACES APART WITH AID OF BLUNT EDGE. DO NOT TRY TO PULL SURFACES APART WITH A DI

RECT OPPOSING ACTION. EYES: WASH WITH WARM WAT ER AND APPLY A GAUZE PATCH. EYE WILL OPEN WITHOUT FURTHER ACTION, TYPICALLY IN 1-4 DAYS. MOUTH: APPLY LOTS OF WARM WATER TO LIPS. PEEL OR ROLL LIPS APART. DO NOT PULL WITH DIRECT FORCE.SEE SUPP DATA.

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

Spill Release Procedures: FLOOD WITH WATER TO POLYMERIZE COMPLETELY. SOAK UP WITH AN INERT ABSORBENT.

Neutraliz

ing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: POLYMERIZE WITH WATER. INCINERATE IN ACCORDANCE WITH

EPA AND LOCAL REGULATIONS.

Handling And Storage Precautions: STORE AT OR BELOW 75F TO PRESERVE SHELF LIFE.

AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

\_\_\_\_\_

Fire and Explosion Hazard Information

\_\_\_\_\_

Flash Poin t Method: TCC

Flash Point Text: 150F,66C Lower Limits: UNKNOWN Upper Limits: UNKNOWN

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL

FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS

DECOMPOSITION PRODUCTS AND VAPORS.

Control Measures

\_\_\_\_\_

\_\_\_\_\_

Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.

Ventilation: POSITIVE DOWN-DRAFT EXHAUST VENTILATION SHOULD BE PROVIDED TO

MAINTAIN VAPOR CONCENTRATION BELOW TLV.

Protective Gloves: POLYETHYLENE GLOVES. DO NOT USE COTTON.

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: SAFETY SHOWER AND EYE WASH STATION. Work Hygienic Practices: HANDLE CAREFULLY. AVOID SKIN CONTACT.

Supplemental Safety and Health: IT IS ALMOST IMPOSSIBLE TO SWALLOW PRO

## DUCT.

PRODUCT WILL SOLIDIFY IN MOUTH. CYANOACRYLATES GIVE OFF HEAT ON SOLIDIFICATION. IN RARE CASES A DROP WILL CAUSE A BURN. BURNS SHOULD BE TREATED NORMALLY AFT ER THE LUMP OF CYANOACRYLATE IS RELEASED FROM THE TISSUE AS DESCRIBED IN FIRST AID SECTION.

Physical/Chemical Properties
HCC: V4 B.P. Text: >300F,>149C M.P/F.P Text: UNKNOWN Decomp Text: UNKNOWN Vapor Pres: < ; 0.2 Vapor Density: 3 Spec Gravity: 1.09 Viscosity: UNKNOWN Evaporation Rate & Reference: UNKNOWN Solubility in Water: POLYMERIZED BY WATER Appearance and Odor: CLEAR LIQUID, PUNGENT ODOR Corrosion Rate: UNKNOWN
Reactivity Data
======================================
ALKALIES. Hazardous Decomposition Products: IRRITATING ORGANIC VAPORS Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NONE. WILL NOT OCCUR.
======================================
======================================
= MSDS Transport Information ====================================
======================================
======================================
======================================
Respons

ible Party Cage: 05972 Trans ID NO: 109652

Product ID: QUICK SET 404 INDUSTRIAL ADHESIVE SPLICING

MSDS Prepared Date: 01/28/1991

Review Date: 03/18/1991

MFN: 3

Net Unit Weight: UNKNOWN Multiple KIT Number: 0

Kit Part IND: Y Review IND: Y Unit Of Issue: KT Container QTY: 1

Type Of Container: UNKNOWN

Additional Data: THIS IS PART OF A KIT. PART B IS THE MOST HAZARDOUS COMPONENT

AND THEREFORE GOVERNS SHIPPING. SHIPPI NG CODES WHEN SHIPPED AS COMPLETE KIT:

LESS THAN 1 PINT OF PART B - DTJ; ZZZ; ZZZ; CZQ (ORM-D CONSUMER COMMODITY). MORE THAN 1 PINT PART B-NAX; OSR; YEL; JKT.

\_\_\_\_\_

**Detail DOT Information** 

\_\_\_\_\_\_

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail IMO Information** 

\_\_\_\_\_

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATE D FOR THIS MODE OF TRANSPORTATION

\_\_\_\_\_

**Detail IATA Information** 

\_\_\_\_\_

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

\_\_\_\_\_

Detail AFI Information

\_\_\_\_\_

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

==========

\_\_\_\_\_

## **HAZCOM Label**

\_\_\_\_\_\_

Product ID: QUICK SET 404 INDUSTRIAL ADHESIVE SPLICING

Cage: 05972

Company Name: LOCTITE CORPORATION Street: 1001 TROUT BROOK CROSSING

City: ROCKY HILL CT Zipcode: 06067-3910

Health Emergency Phone: 203-278-1280

Label Required IND: Y

Date Of Label Review: 03/18/1991

Status Code: C

MFG Label NO: NONE Label Date: 03/18/1991 Origination Code: F Chronic Hazard IND: Y Eye Protection IND: Y

ES

Skin Protection IND: YES Signal Word: WARNING Health Hazard: Slight Contact Hazard: Moderate

Fire Hazard: Slight Reactivity Hazard: Slight

Hazard And Precautions: STORE AT OR BELOW 75F TO PRESERVE SHELF LIFE. AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR. FIRST AID: SKIN: IMMERSE THE BONDED SURFACES IN WARM SOAPY WATER. PEEL OR ROOL THE SURFACES APART WITH AID OF BLUNT EDGE. DO NOT TRY TO PULL SURFACES APART WITH A DIRECT OPPOSING ACTION. EYES: WASH WITH WARM WATER AND APPL

Y A GAUZE PATCH. EYE WILL

OPEN WITHOUT FURTHER ACTION, TYPICALLY IN 1-4 DAY S. MOUTH: APPLY LOTS OF WARM WATER TO LIPS. PEEL OR ROLL LIPS APART. DO NOT PULL WITH DIRECT FORCE.SEE MSDS FOR ADDITIONAL INFORMATION.

\_\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility f

or the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.