

VIMASCO CORPORATION -- LAGGING ADHESIVE&COAT P/N 713 WHITE GRADE A --
8040-00-273-8707

=====
===== Product Identification =====

Product ID:LAGGING ADHESIVE&COAT P/N 713 WHITE GRADE A

MSDS Date:02/09/1990

FSC:8040

NIIN:00-273-8707

MSDS Number: BJQQQ

=== Responsible Party ===

Company Name:VIMASCO CORPORATION

Box:516

City:NITRO

State:WV

ZIP:25143

Country:US

Info Phone Num:304-755-3328

Emergency Phone Num:3

04-755-3328

Preparer's Name:JOHN TIDQUIST

CAGE:DO737

=== Contractor Identification ===

Company Name:VIMASCO CORP

Box:516

City:NITRO

State:WV

ZIP:25143

Country:US

Phone:304-755-3328

CAGE:14947

Company Name:VIMASCO CORPORATION

Address:PO BOX 516

Box:516

City:NITRO

State:WV

ZIP:25143

Phone:304-755-3328

CAGE:DO737

=====
===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: < 2%

Other REC Limits:NONE SPE

CIFIED
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHLORINATED PARAFFIN
CAS:63449-39-8
Fraction by Wt: < 10%
Other REC Limits:NONE SPECIFIED

Ingred Name:VINYL ACETATE (SARA III)
CAS:108-05-4
RTECS #:AK0875000
Fraction by Wt: < 0.2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15,A3 STEL;93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt: < 4%
Other REC Limits:NONE SPECIFIED
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9192

Ingred Name:VOC = 45G/LIT 370LB/GL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ETHYLENE GLYCOL:INGESTION CAUSES
DRUNKENNESS, RAPIDLY PASSING INTO COMA,WITH

SERIOUS KIDNEY

INJURY/DEATH.CHLORINATED PARAFFIN:SLIGHT HAZARD WITH THE LIVER AS TARGET ORGAN.VINYL ACETATE:SLIGHT RESIDUAL MONOMER CAUSE EYE AND RESPIRATORY IRRITATION.HEXYLENE GLYCOL:LARGE ORAL DOSES PRODUCE NARCOSIS.

Explanation of Carcinogenicity:VINYL ACETATE HAS BEEN REPORTED TO CAUSE CANCER IN LABORATORY ANIMALS.

Effects of Overexposure:ETHYLENE GLYCOL:CAUSE SKIN AND EYE IRRITATION.EXCESSIVE INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION.HEXYLENE GLYCOL:

IN HIGH CONCENTRATIONS, CAN BE AN IRRITANT TO EYES,SKIN AND MUCOUS MEMBRAN ES.

Medical Cond Aggravated by Exposure:NONE KNOWN

=====
First Aid Measures
=====

First Aid:SKIN:WASH WITH SOAP AND WATER.EYES:FLUSH WITH CLEAN WATER AT LEAST 15 MINUTES.IF IRRITATION PERSISTS,CONSULT PHYSICIAN.INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,ADMINISTER OXYGEN.IF IRR ITATION PERSISTS,CONSULT PHYSICIAN.INGESTION:GIVE TWO GLASSES OF WATER,I

NDUCE VOMITING.CONSULT PHYSICIAN OR POISON CONTROL CENTER.NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:NONE

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:PRODUCT WILL NOT BURN UNTIL AFTER BOILED OR EVAPORATED. FOR DRIED FILM OR RESIDUAL SOLIDS, FULL PROTECTIVE EQUIPMENT IS RECOMMENDED, INCLUDING SCBA.

Unusual Fire/Expl

osion Hazard:NONE KNOWN

=====
Accidental Release Measures
=====

Spill Release Procedures:MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL. MINOR SPILLS MAY BE FLUSHED TO SEWER IF REGULATIONS PERMIT. BEFORE DRYING, PRODUCT MAY BE WASHED AWAY WITH WATER; AFTER DRYING, REMOVE WITH A PAINT SCRAP ER OR STRONG SOLVENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID BREATHING VAPORS.APPLICATION TO

H

OT SURFACES MAY BE IRRITATING.KEEP CONATAINER CLOSED USE ADEQUATE VENTILATION.STORE INDOORS AT TEMPS OF 45-90F.

Other Precautions:FOR INDUSTRY/PROFESSIONAL USE ONLY.NOT INTENDED FOR RETAIL SALE OR USE BY INDIVIDUAL CONSUMER.DO NOT REUSE CONTAINER FOR POTABLE OR EDIBLES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED AREAS,USE APPROVED CHEMICAL VAPOR RESPIRATOR.IN APLICATIONS WHERE MISTS OR SPRAY ARE GENERATED,AVOID

INHALATION OF AIRBORNE PARTICULATES BY USING AN APPROVED RESPIRATOR WITH ORGANIC VAPO R CARTRIDGE WITH PREFILTER FOR MIST/DUST

Ventilation:GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:GOGGLES, FACESHIELD

Other Protective Equipment:NONE

Work Hygienic Practices:THOROUGHLY CLEANSE HANDS AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemica
l Properties =====

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:25F/-4C

Decomp Temp:Decomp Text:240F,116C

Vapor Density:< THAN AIR

Spec Gravity:1.29

pH:8 - 9

Viscosity:75,000CEN

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:APPRECIABLE

Appearance and Odor:VISCOUS, WHITE OR RED PASTE WITH MILD LATEX ODOR.

Percent Volatiles by Volume:60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:

YES

MATERIALS INCOMPATIBLE WITH WATER.

Stability Condition to Avoid:NONE KNOWN

Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL YIELD CO,
CO₂, HCL, ANTIMONY-OXYCHLORIDE AND FRAGMENTED SHORT-CHAIN
HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.
REVIEW HAZARD SECTION OF THIS SHEET BEFORE ATTEMPTING CLEANUP.
EMPTY CONTAINERS ARE NON HAZARDOUS UNDER RCRA AS INDUSTRIAL
WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular
situation.