

ARMSTRONG PRODUCTS CO DIV OF POLYMER INDUSTRIES -- A36 PART A ADHESIVE RESIN --
8040-00-273-8710

===== Product Identification =====

Product ID:A36 PART A ADHESIVE RESIN

MSDS Date:10/01/1985

FSC:8040

NIIN:00-273-8710

Kit Part:Y

MSDS Number: BJQQR

=== Responsible Party ===

Company Name:ARMSTRONG PRODUCTS CO DIV OF POLYMER INDUSTRIES

Address:407 ARGONNE RD

Box:657

City:WARSAW

State:IN

ZIP:46580-3811

Country:US

Info Phone Num:219-267-3226 OR 219-267-5375

Emergency Phone Num:219-267-3226 OR 219-267-5375

Preparer's Name:STEVEN L. KIEFER

CAGE:DO043

=== Contractor Identification ===

Company Name:ARMSTRONG PRODUCTS CO

Box:647

City:WARSAW

State:IN

ZIP:46580

Phone:219-267-3226 OR 219-267-5375

CAGE:DO043

Company Name:MORTON THIOKOL,INC;ARMSTRONG PRODUCTS COMPANY

Address:407-ARGONNE ROAD

Box:647

City:WARSAW

State:IN

ZIP:46580-3811

Country:US

Phone:219-267-3226

CAGE:98911

===== Composition/I

Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENTS
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 GREATER THAN 2000MG/KG-RATS
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:SKIN:ONLY ON PROLONGED OR REPEATED
CONTACT.EYE:MINOR TRANSIENT IRRITANT.

===== First Aid Measures =====

First Aid:INHALATION:MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT,GET PROMPT MEDICAL ATTENTION. EYE CONTACT:FLUSH EYES WITH LARGE VOLUMES OF WATER. IF IRRITATION PERSISTS,GET MEDICAL ATTENTION. SKIN CONTACT:WASH THOROUGHLY WITH SOAP AND WATER. IF PERSISTENT IRRITATION OCCURS,GET MEDICAL ATTENTION. INGESTION:IF CONSCIOUS INDUCE VOMITING.GET MEDICAL ATTENTION.CONTACT NEAREST REGIONAL POISON CONTROL CENTER.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:480F,249C
Extinguishing Media:CARBON DIOXIDE, WATER, FOAM, DRY CHEMICAL, SAND.
Fire Fighting Procedures:WATER IS MOST EFFECTIVE AS MIST OR SPRAY. WEAR NIOSH/MSHA APPROVED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARDS

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH ABSORBENT MATERIAL. SCOOP UP.

===== Handling and Storage =====

Handling and Storage Prec

autions:STORE IN COOL, DRY PLACE.

Other Precautions:AVOID INHALATION OF FUMES OF HEATED MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION IF MATERIAL IS HEATED. COMPLY WITH OSHA 29 CFR 1910.134.

Ventilation:PROVIDE VENTILATION IF MATERIAL IS HEATED.

Protective Gloves:PLASTIC OR RUBBER GLOVES PREFERRED.

Eye Protection:USE GOGGLES FOR EYE PROTECTION.

Other Protective Equipment:OTHER EQUIPMENT AS NECESSARY TO MINIMIZE

CONTACT WITH SKIN, EYES AND STREET CLOTHES.

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING, SMOKING OR USING THE TOILET.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:46.4F,8.0C

Spec Gravity:1.20+- .05

Solubility in Water:NIL

Appearance and Odor:AMBER LIQUID SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid

:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:FREEZING, OPEN FLAME

Hazardous Decomposition Products:CARBON MONOXIDE,ALDEHYDES,AND OTHER ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.