View NSN Online: https://aerobasegroup.es/nsn/8010-00-165-4420

BAKER SEALANTS & COATINGS COMPANY -- TT-V-71H, FLOOR AND TRIM VARNISH 8010-00-165-4420

Product ID:TT-V-71H, FLOOR AND TRIM VARNISH MSDS Date:04/19/1989 FSC:8010 NIIN:00-165-4420 MSDS Number: BJXHC === Responsible Party === **Company Name: BAKER SEALANTS & COATINGS COMPANY** Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Nu m:201-333-6986 Emergency Phone Num:201-333-6986 CAGE:FO833 === Contractor Identification === Company Name: BAKER SEALANTS & COATINGS CO., INC. Address:234 SUYDAM AVENUE Box:B City: JERSEY CITY State:NJ ZIP:07304-3306 Phone: (201) 333-6986 CAGE:FO833 Company Name: BAKER SEALANTS AND COATINGS CO Address:234 SUYDAM AVE Box:City:JERSEY CITY State:NJ ZIP:07304-3306 Country:US Phone:201-333-6986 CAGE:34094 Company Name: STEVEN INDUSTRIES Address:39 AVENUE C Box:8 City:BAYONNE State:NJ ZIP:07002-3417 Countr

y:US Phone:201-437-6501 CAGE:33150

Ingred Name:MINERAL SPIRITS, EXEMPT CAS:64742-88-7 Fraction by Wt: 54% Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:125 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:INHALATION:IN EXTREME CASES.UNCONSCIOUSNESS AND DEATH MAY OCCUR.INGESTION:INGESTION OF

PRODUCT MAY RESULT IN VOMITING.ASPIRATION OF VOMITUS INTO THE LUNGS MUST BE AVOIDED AS EVEN SMALL QUANTITIES MAY RESULT IN ASPIRATION PNEUMONITIS WHICH MAY BE EVIDENCED BY COUGHING,LABORED BREATHING AND CYANOSIS.IN SEVERE CASES:DEATH Effects of Overexposure:EYES:HIGH CONCENTRATIONS MAY BE

IRRITATING.SKIN:SLIGHTLY IRRITATING.PROLONGED EXPO MAY CAUSE DEFATTING/DRYING OF SKIN,LEADING TO IRRITATION/DERMATITIS.INHALE:HIGH CONCENTRATIONS MAY BE IRRIT TO

NOSE,R ESPIRATORY T

RACT AND MAY CAUSE CENTRAL NERVOUS SYSTEM

DEPRESSION, EVIDENCED BY GIDDINESS HEADACHE, DIZZINESS AND NAUSEA. Medical Cond Aggravated by Exposure: PREXISTING EYE, SKIN AND

RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYE:FLUSH W/WATER FOR 15 MIN WHILE HOLD EYELIDS OPEN.GEN MED ATTN.SKIN:FLUSH W/WATER.REMOVE CONTAMINATED CLOTHES/SHOES.WASH W/SOAP/WATER.DO NOT REUSE CLOTHES/SHOE

S UNTIL CLEANED.IF IRRIT PERSISTS,GET MED ATTN.INHALE:REMOVE TO FRESH AIR/PROVIDE OXYGEN IF BREATHING DIFFICULT.GIVE CPR IF NOT BREATHING.GET MED AID.INGESTION:DO NOT INDUCE VOMIT.IF VOMIT OCCURS SPONTANEOUSLY,KEEP HEAD BELOW HIPS.*

Flash Point Method:TCC Flash Point:105F/41C Lower Limits:1 Upper Limits:6 Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE. Fire Fighting Procedures:DO NOT ENTE

R SPACE W/OUT FULL BUNKER GEAR,INCLUDE POSITIVE PRESS NIOSH APPROVE SCBA.COOL FIRE EXPOSE CONTAINER W/H2O.DO NOT USE DIRECT STRM OF H2O ON POOL FIRES Unusual Fire/Explosion Hazard:CONTAINER EXPOSED TO HIGH HEAT FROM FIRE SHOULD BE COOLED W/WATER TO PREVENT VAPOR PRESS BUILD-UP.COOL CONTAINER AREAS EXPOSED TO DIR FLAME W/LARGE QUANT WATER.
======================================
Spill Release Procedures:REMOVE SOURCES OF IGNIT.WEAR APPROPRIATE RES
PIRATOR/PROTECT CLOTH.SHUT OFF SOURCE IF SAFE.DIKE/CONTAIN.REMOVE W/VACUUM TRUCKS/PUMP TO STORAGE/SALVAGE VESSEL.SOAK UP W/ABSORBENT.PLACE IN NON-LEAK CONTA INER/SEALED TIGHTLY FOR DISPOSE.FLUSH AREA W/WATER
======================================
 Handling and Storage Precautions: THIS PRODUCT IS CLASSIFIED AS AN OIL.SPILLS INTO SURFACE WATERS, AIR OR LAND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER 1-800-424-8802. Other Precautions: VAPORS MAY ACCUMULATE/TRAVEL TO IGNIT SOURCES DISTANT FROM THE HANDLING SITE.KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT CUT, DRILL, GRIND, WELD, ETC. ON/NEAR CONTAINERS. SURFACES THAT ARE SUFFICIENTLY HO T MAY IGNIT PRODUCT IN ABSENCE OF SPARK.
======================================
Respiratory Protection: IF EXPOSURE DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVEREXPOSURE.USE EITHER AN ATMOSPHERE SUPPLYING RESPIRATOR OR AN AIR PURIFYING RESPIRATOR FO R ORGANIC VAPORS. Ventilation: USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS WITHIN SUGGESTED PEL/TLV LIMITATIONS. Protective Gloves: WEAR CHEMICAL RESISTANT GLOVES Eye Protection: WEAR SAFETY GLASSES OR GOGGLES Other Protective Equipment: SAFETY SHOWER, EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE. Work Hygienic Practices: WASH WITH SOAP/WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.N

Evaporation Rate & amp; Reference: SLOWER THAN ETHER

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE.
Stability Condition to Avoid:AVOID HEAT, FLAME
Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS DURING COMB
USTION.

Waste Disposal Methods:SEAL CONTAINERS,LABEL PROPERLY AND DISPATCH TO APPROVED WASTE DISPOSAL FACILITY.ASSURE COMPLIANCE WITH ALL LOCAL,STATE AND FEDERAL REGULATIONS.IF THIS PRODUCT BECOMES A WASTE MATERIAL,IT WOULD BE IGNI TABLE HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.