View NSN Online: https://aerobasegroup.es/nsn/8030-01-134-6513

Product ID:WC-2240, COMPOUND VEHI BODY SEALER/DEADENER MSDS Date:03/26/1990 FSC:8030 NIIN:01-134-6513 MSDS Number: BJXSJ === Responsible Party === Company Name: WIDGER CHEMICAL COMPANY Address:13650 EAST TEN MILE ROAD Box:306 **City:WARREN** State:MI ZIP:48089 Country:US Info Ph one Num:313-776-5000 Emergency Phone Num:313-776-5000 Preparer's Name:MIKE PELLNY CAGE:WIDGE === Contractor Identification === Company Name: WIDGER CHEMICAL COMPANY Address:13650 EAST TEN MILE ROAD Box:306 **City:WARREN** State:MI ZIP:48089 Country:US Phone:313-776-5000 CAGE:WIDGE

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 45-55% Other REC Limits:NONE SPECIFIED OSHA PEL:300 PPM/400 STEL ACG IH TLV:300 PPM; 9192

Ingred Name:PARAFFIN WAX CAS:8002-74-2 RTECS #:RV0350000 Fraction by Wt: 25-35% Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 (FUME) ACGIH TLV:2 MG/M3 (FUME); 9192

Ingred Name:GRAPHITE, SYNTHETIC CAS:7440-44-0 RTECS #:FF5250100 Fraction by Wt: 2-5% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:HYDRO-TREATED ALIPHATIC OIL CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 2-5% Other REC Limits:NONE SPECIFIED

Ingred Name :CALCIUM SULFONATE BASED CORROSION INHIBITOR (CALCIUM SULFONATE PLUS OIL, WAX, AND/OR SOLVENT LISTED ABOVE.) CAS:61789-86-4 RTECS #:WR7140000 Fraction by Wt: 10-20% Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 3.3 LB/GL RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Health Hazards Acute and Chronic:MAY CAUSE HEADACHES OR NAUSEA, EYE IRRITATION IF SPLASHED I

## NTO THE EYE, DEFATTING OF SKIN. THRESHOLD LIMIT: TWA 100 PPM; OTHER LIMIT: MAC 500 PPM.

======================================
First Aid:INHALATION: REMOVE PERSON TO FRESH AIR. SKIN: CLEAN AFFECTED AREA. EYES: CLEAN AFFECTED AREA WITH EYE WASH AND CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN. NOTE TO PHYSICIAN: TREAT FOR SOLVENT ING ESTION.
======================================
Flash Point:NR Lower Limits:0.7 Upp er Limits:6.0 Extinguishing Media:USE CO2, DRY CHEMICAL, FOAM. Fire Fighting Procedures:VAPORS HEAVIER THAN AIR. WATER MAY CAUSE FROTHING.
======================================
Spill Release Procedures:USE ABSORBENT, DIKE LARGE SPILLS, AVOID USE OF SPARKS OR OPEN FLAMES, VENTILATE WELL. USE NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions: AVOID OPEN SPARKS OR FLAMES. STORE ABOVE 40F.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection: IF MAC OF 500 PPM IS EXCEEDED, USE CHARCOAL TYPE.
Ventilation:NOT REQUIRED. Eye Protection:USE SAFETY GLASSES. Other Protective Equipment:USE PROTECTIVE CLOTHING FOR CLEANLINESS AS DESIRED. Supplemental Safety and Health
======================================
HCC:V3 Boiling Pt:B.P. Text:313F,156C Vapor Pres:2.6

Vapor Pres:2.6 Vapor Density:+1 Spec Gravity:0.815 Evaporation R ate & Reference:0.12 (TOLUENE) Appearance and Odor:BLACK PASTE, MILD SOLVENT ODOR. Percent Volatiles by Volume:59

Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS. Stability Condition to Avoid:AVOID OPEN FLAMES Hazardous Decomposition Products:CO, CO2, H20. Conditions to Avoid Polymerization:OPEN FLAMES AND/OR SPARKS.

Waste Dispos

al Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume

responsibility for the suitability of this information to their particular situation.