

ASHLAND CHEMICAL INC SUBSIDIARY OF ASHLAND OIL INC -- LITTON LACQUER THINNER --  
8010-00-160-5788

=====  
===== Product Identification =====

Product ID:LITTON LACQUER THINNER

MSDS Date:05/31/1989

FSC:8010

NIIN:00-160-5788

MSDS Number: BJYDX

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL INC SUBSIDIARY OF ASHLAND OIL INC

Box:22219

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Info Phone Num:614-889-333

8

Emergency Phone Num:800-274-5263

CAGE:7L600

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO DIV OF ASHLAND OIL INC

Address:3849 FISHER RD

Box:2219

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Phone:614-790-3333 / 800-325-3751

CAGE:7L600

=====  
===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 21%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/

75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 49%  
Other REC Limits:\*  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 11%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:150 PPM/200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHO  
L (SARA III)  
CAS:71-36-3  
RTECS #:EO1400000  
Fraction by Wt: 11%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:S, C 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 1-10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Health

Hazards Acute and Chronic:OVEREXPOSURE HAS BEEN BEEN SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN HUMANS:KIDNEY DAMAGE, EYE DAMAGE, LIVER ABNORMALITIES. EYES: SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: MODE RATE IRRITATION.

Effects of Overexposure:EYES:SEVERE IRRIT,RED,TEAR,BLURRED VISION.SKIN:MODERATE IRRIT,DEFATTING,DERMATITIS.BREATHING:NASAL & RSPRTRY IRRIT,CNTRL NERVE SYSTEM EFFECTS,DIZZI,WEAK,FATIGUE,NAUSEA,HEADACHE/POSS UNCONSCIOUSNESS/DE AT

H.SWALLOWING:GASTROINTESTINAL IRRIT,NAUSEA,VOMIT/DIARRHEA.ASPIRATION OF MAT'L INTO LUNGS CAN CAUSE CHEM PNEUMONITIS.

===== First Aid Measures =====

First Aid:SKIN:THOROUGHLY WASH AREA W/SOAP/WATER.REMOVE CONTAM CLOTHES.WASH BEFORE RE-USE.REMOVE CONTAM SHOES/DISCARD.EYES:FLUSH W/LOTS OF WATER,LIFTING UPPER/LOWER LIDS OCCASIONALLY.GET MED ATTN.SWALLOWED.DO N OT INDUCE VOMIT.KEEP PERSON WARM/QUIET.GET MED ATTN.BREATHED:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN.IF BREATHING HAS STOPPED,GIVE CPR.KEEP PERSON WARM,QUIET AND GET MED ATTN.

===== Fire Fighting Measures =====

Flash Point:< 73F/< 23C

Lower Limits:1.2

Extinguishing Media:REGULAR FOAM OR WATER FOG OR CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

Unusual Fire/Exp

losion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION & IGNITED BY IGNIT SOURCES AT LOCATIONS DISTANT FROM MAT'L HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORB/OTHER ABSORB MAT'L & TRANSFER TO HOOD.ELIMINATE IGNIT SOURCES.PERSONS NOT WEARING PROTECT EQUIP,EXCLUDE FROM AREA.STOP SPILL AT SOURCE,DIKE AREA,PUMP LI QUID TO SA

LVAGE TANK.SHOVEL  
REMAINING TO CONTAINER

=====  
Handling and Storage  
=====

Other Precautions:CONTAINERS OF THIS MAT'L MAY BE HAZARDOUS WHEN  
EMPTIED,SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES,ALL HAZARD  
PRECAUTIONS MUST BE OBSERVED.NEVER USE WELDING OR CUTTING TORCH ON  
OR NEAR DRUM(EVEN EMPTY BECAUSE IT CAN IGNIT EXPLOSIVELY.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF WORKPLACE EXPOS LI  
MIT OF PRODUCT/ANY

COMPONENT IS EXCEEDED,AN AIR SUPPLIED RSPRTR IS ADVISED IN ABSENCE  
OF PROPER ENVIRONMENTAL CONTROL.OSHA REGS ALSO PERMIT OTHER RSPRTRS  
UNDER SPECIFIED CONDITION S.USE ADMIN CONTROLS TO REDUCE EXPOSURE.

Ventilation:PROVIDE SUFFICIENT MECHANICAL(GENERAL AND/OR LOCAL  
EXHAUST)VENTILATION TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:WEAR NITRILE RUBBER GLOVES.

Eye Protection:CHEM SPLASH GOGGLES/OTHER SAFETY GLASSES

Other Protective Equipment:TO PREVENT REPEAT  
ED OR PROLONGED SKIN

CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F3

Boiling Pt:B.P. Text:180F,82C

Vapor Pres:33 MM HG

Vapor Density:> AIR

Spec Gravity:< WATER

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:100

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous

Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:ALLOW VOLATILE PORTION TO EVAP IN HOOD.ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETE CLEAR HOOD DUCT WORK.DESTROY BY LIQUID INCINERATION IN ACCORD W/APPLIC REGS.CONTAM ABSORB MAY BE DEPOSITED IN A LAND FILL IN ACCORDANCE W/LOCAL,STATE, & FEDERAL REGS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.