

VISILOX SYSTEMS INC. -- V-724 SILICONE COMPOUND -- 6850-00-880-7616

===== Product Identification =====

Product ID:V-724 SILICONE COMPOUND

MSDS Date:07/12/1989

FSC:6850

NIIN:00-880-7616

MSDS Number: BJYKF

=== Responsible Party ===

Company Name:VISILOX SYSTEMS INC.

Address:RT 355 SICHIO DR

Box:1344

City:POESTENKILL

State:NY

ZIP:12140

Country:US

Info Phone Num:800-423-9993

Emergency Phone Num:518-283

-5963

Preparer's Name:JASON E BARNES

CAGE:64101

=== Contractor Identification ===

Company Name:CARLSON R H CO- NORTHERN LABS DIV

Address:41 CHESTNUT ST

Box:City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500(73)FAX -0032 (JACKIE)

CAGE:2L329

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

Company Name:VISILOX SYSTEMS INC

Address:RT 355 SICHIO DR RR 1

Box:1344

City:POESTENKIL

L
State:NY
ZIP:12140
Country:US
Phone:800-423-9993
CAGE:64101

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE:MAY BE MILDLY IRRITATING.

SKIN:

RELEASE DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL NECROSIS. INHALATION:NOT EXPECTED TO BE A RELEVANT ROUTE OF EXP OSURE; HIGH TEMPERATURE VAPORS IRRITATERESPIRATORY TRACT. INGESTION: LOW LEVEL OF TOXICITY. CHRONIC: SKIN DISORDERS.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. LOCAL

NECROSIS IS EVIDENCED BY DELAYED ONSET OF PAIN

AND TISSUE DAMAGE A FEW HOURS FOLLOWING INJECTION.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION. EYE: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: W

ASH WITH S OAP & WATER/WATERLESS CLEANER. REMOVE CONTAMINATED CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IN GENERAL, NO TREATMENT IS REQUIRED. GET MEDICAL ADVICE.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>500F,>260C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL

FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS, LIKE CO, CO2, SI02
DUST

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. CLEAN AREA WITH
APPROPRIATE CLEANER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH
ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN
USE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES.
Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP & WATER BEFORE
EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRER
CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF
CONTAMINATED LEATHER ARTICLES (SHOES) THAT CAN NOT BE
DECONTAMINATED

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION
EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS AS
PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS. RESPIRATORY
PROTECTION NOT ORDINARILY R EQUIRED.
Ventilation:NONE REQUIRED
Protective Gloves:NEOPRENE RUBBER AS REQUIRED.
Eye Protection:SAFETY GLASSES RECOMMENDED.
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.
Supplemental Safety and Health
DO NOT GET IN EYES OR ON CLOTHING.

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:1.03
pH:NEUTRL
Solubility in Water:NEGLIGIBLE
Appearance and Odor:TRANSLUCENT-WHITE PASTE, LITTLE OR NO ODOR
Percent Volatiles by Volume: