

MOBIL OIL CORP -- MOBIL DTE OIL HEAVY MEDIUM -- 9150-00-027-3098

===== Product Identification =====

Product ID:MOBIL DTE OIL HEAVY MEDIUM

MSDS Date:02/28/1991

FSC:9150

NIIN:00-027-3098

MSDS Number: BJYQB

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-424-9300

Emergency Phone Num:703-849-3265 OR 212-883-4411

CAGE:3U728

=== Contractor Identification ===

Company Na

me:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWES ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: >95.00

%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS SLIGHTLY TOXIC
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Over
exposure:EFFECTS OF OVEREXPOSURE: SLIGHT SKIN
IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER. SKIN: WASH CONTACTED AREA WITH SOAP
AND WATER. INHALATION: NOT EXPECTED TO BE A PROBLEM. INGESTION: NOT
EXPECTED TO BE A PROBLEM HOWEVER, IF GREATER THAN 1/2 LITER (PINT)
INGEST ED, IMMEDIATELY GIVE 1 TO 2 GLASSES OF WATER AND CALL A
PHYSICIA. DO NOT
INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>400F,>204C
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS FOR
ENCLOSED AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
PREVENT RUNOFF OR DILUTION FROM ENTERING WATERWAYS.
Unusua

I Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,
DIATOMACEOUS EARTH, ETC. SHOVEL UP & DISPOSE OF AT AN APPROPRIATE
WASTE DISPOSAL FACILITY.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE
AND WITH ADEQUATE VENTILATION.
Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED.
Eye Protection:NO SPECIAL EQUIPMENT REQUIRED.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:GOOD PERSONAL HYGIENE SHOULD ALWAYS BE
FOLLOWED.
Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Vapor Pres: