

CSD INC. (OBSOLETE ADDRESS; USE 4N760) -- THINNER, PAINT TYPE I-REG MINERAL SPIRITS --
8010-00-558-7026

===== Product Identification =====

Product ID:THINNER, PAINT TYPE I-REG MINERAL SPIRITS
MSDS Date:09/01/1990
FSC:8010
NIIN:00-558-7026
MSDS Number: BJYZD
=== Responsible Party ===
Company Name:CSD INC. (OBSOLETE ADDRESS; USE 4N760)
Address:420 SEABOARD DRIVE
City:MATTHEWS
State:NC
ZIP:28105-5073
Country:US
Info Phone Num:704-821-9822
Emergency Phone Num:704-
821-9822
Preparer's Name:DAVID SHIPP
CAGE:5W216
=== Contractor Identification ===
Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)
Address:420 SEABOARD DRIVE
Box:City:MATTHEWS
State:NC
ZIP:28105-5073
Country:US
Phone:704-821-9822
CAGE:5W216

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

Ingred Name:1,2,4 TRIMETHYL B

ENZENES (SARA 313)
CAS:95-63-6
RTECS #:9999999ZZ
Fraction by Wt: 2% MAX
Other REC Limits:NONE SPECIFIED
OSHA PEL:125 MG/M3
ACGIH TLV:125 MG/M3

===== Hazards Identification =====

Effects of Overexposure:EYE:IRRIT.SKIN:IRRIT,INHALATION:IRRIT TO
RESPIRATORY TRACT,HEADACHES AND DIZZINESS,ARE ANESTHETIC AND MAY
HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS.INGESTION:SMALL AMOUNTS
ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION INDUCED BY
VOMITIN
G,MAY CAUSE BRONCHIOPNEUMONIA OR PULMONARY EDEMA.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/LOTS OF WATER UNTIL IRRIT SUBSIDES.IF IRRIT
PERSISTS,GET MED ATTN.SKIN:FLUSH W/LOTS OF WATER/SOAP IF
AVAILABLE.REMOVE GROSSLY CONTAM CLOTHING,INCLUDE SHOES.LAUNDER
BEFORE RE-USE.INHALATION :USING PROPER RESPIRATORY PROTECT,IMMED REMOVE
VICTIM FROM EXPOS.ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING IS
STOPPED.KEEP AT REST.GET MED ATTN.ING
ESTED:DO NOT INDUCE VOMIT.KEEP
AT REST.GET MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:100F/38C
Autoignition Temp:Autoignition Temp Text:490F
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:USE FOAM,DRY CHEMICAL OR WATER SPRAY
Fire Fighting Procedures:USE H2O SPRAY TO COOL FIRE EXPOS
SURFACE/PROTECT PERSON.ISOLATE FUEL SUPPLY FROM FIRE.AVOID SPRAYING
H2O DIRECTLY INTO STORAGE CONTAINER DUE TO DANGER/BOILOVER
R.
Unusual Fire/Explosion Hazard:COMBUST LIQUID CAN FORM COMBUST MIX AT
TEMPS AT/ABOVE FLASHPOINT.STATIC DISCHARGE,MAT'L CAN ACCUMULATE
STATIC CHARGES WHICH CAN CAUSE INCENDARY ELEC DISCHARGE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM SOURCES OF IGNIT.PREVENT ADD DISCHARGE OF
MAT'L.IF IN PUBLIC AREA,KEEP PUBLIC AWAY/ADVISE AUTHORITY.PREVENT
LIQUID FROM ENTERING SEWERS,WATERCOURSES/LOW AREA.CONTAIN SPILLED
LIQUID W/SAND/

EARTH.DO NOT USE COMBUST MATERIAL.RECOVER BY PUMPING.

===== Handling and Storage =====

Handling and Storage Precautions:LABORATORY SAMPLES SHOULD BE STORED AND HANDLED IN A LAB HOOD.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. CONTAINERS RETAIN PRODUCT RESIDUES AND ALL HAZARDOUS PRECAUTION MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE CONCENTRATIONS IN AIR MAY EXCEED THE LIMITS AND ENGINEERING WORK PRACTICE OR OTHER MEANS OF EXPOSURE,USE NIOSH/MSHA APPROVED RESPIRATORS TO PREVENT OVEREXPOSURE BY INHALATION

Ventilation:THE USE OF LOCAL EXHAUST VENTILATION IS RECOMMENDED.PROVIDE MECHANICAL VENTILATION IN CONFINED SPACES.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY GLASSES WITH SIDESHIELDS.

Other Protective Equipment:WEAR LONG SLEEVES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:308 TO 396F

Vapor Pres:3.1MMHG

Spec Gravity:0.780

Viscosity:1 CST,79F

Evaporation Rate & Reference:0.1 (N-BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR, LITTLE IF ANY COLOR, SLIGHT OIL ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HALOGENS,MOLTEN SULFUR,STRONG OXIDIZING AGENTS

=====

Disposal Considerations =====

Waste Disposal Methods:CONSULT AN EXPERT ON DISPOSAL OF RECOVERED
MATERIAL AND ENSURE ACCORDANCE WITH LOCAL DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use.

Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.