

NATIONAL CHEMICAL LABORATORIES OF PENNSYLVANIA INC -- WAC FLOOR & MOP TREATMENT,
WAX BASE -- 7930-00-582-4195

===== Product Identification =====

Product ID:WAC FLOOR & MOP TREATMENT, WAX BASE

MSDS Date:07/31/1989

FSC:7930

NIIN:00-582-4195

MSDS Number: BJZWC

=== Responsible Party ===

Company Name:NATIONAL CHEMICAL LABORATORIES OF PENNSYLVANIA INC

Address:401 N 10TH ST

City:PHILADELPHIA

State:PA

ZIP:19123-3803

Country:US

Info Phone Num:215-922-1200

Emergency Pho

ne Num:215-922-1200

Preparer's Name:KDM

CAGE:93607

=== Contractor Identification ===

Company Name:NATIONAL CHEMICAL LABORATORIES OF PENNSYLVANIA INC

Address:401 N 10TH ST

Box:City:PHILADELPHIA

State:PA

ZIP:19123-3803

Country:US

Phone:215-922-1200

CAGE:93607

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Other REC Limits:NONE SPECIFIED

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY80300

00
Other REC Limits:1300 MG/KG
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:POTASSIUM TALLATE
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM PETROLEUM SULFONATE
CAS:68608-26-4
RTECS #:WR7150000
Other REC Limits:NONE SPECIFIED

Ingred Name:OLEIC DIETHANOLAMIDE
Other REC Limits:NONE SPECIFIED

Ingred Name:N-AMYL ACETATE (SARA III)
CAS:628-63-7
RTECS #:AJ1925000
Other REC Limits:4950 MG/KG
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

====
===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE MINOR SKIN & EYE IRRITATION. HARMFUL
IF SWALLOWED, MAY CAUSE SEVERE DIARRHEA.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:FOR EYES:FLUSH WITH WATER UNTIL IRRITATION SUBSIDES. IF
IRRITATION PERSISTS GET MEDICAL ADVICE. FOR SKIN:WASH THOROUGHLY
WITH WATER. IF INGESTED:DO NOT INDUCE VOMITING. GIVE LARGE
QUAN
TITIES OF WATER. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:RECONTAINERIZE BY MOPPING, WET VACUUM OR USE
OF A SUITABLE ABSORBANT. FLUSH REMAINING MATERIAL TO DRAINS. BE
CAUTIOUS OF SLIPPERY FLOORS.

===== Handling and Storage =====

Handling and Storage Prec

autions:STORE BETWEEN 40 & 120F.
Other Precautions:KEEP OUT OF REACH OF CHILDREN. FOR SALE TO, USE &
STORAGE BY SERVICE PERSONNEL ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED
Ventilation:NONE
Protective Gloves:NOT REQUIRED
Eye Protection:GENERALLY NOT REQUIRED
Other Protective Equipment:NONE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,1
00C
Vapor Pres:=TO WATER
Vapor Density:=TO WATER
Spec Gravity:0.936
pH:10.0
Evaporation Rate & Reference:=TO WATER
Solubility in Water:DISPERSES
Appearance and Odor:OPAQUE, THIN, WHITE LIQUID WITH BANANA ODOR
Percent Volatiles by Volume:67.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW LOCAL, STATE & FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify an

d

assume responsibility for the suitability of this information to their particular situation.