

Product ID:X-822 ADHESIVE

MSDS Date:01/30/1990

FSC:8040

NIIN:00-291-8625

MSDS Number: BKHML === Responsible Party ===

Company Name: BAKER SEALANTS & COATINGS CO.

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ ZIP:07304

Info Phone Num:(201) 333-6986

Emergency Phone Num:(201) 333-6986 Preparer's Name:MARIO NAVARRO

CAGE:FO833

=== Contractor Identificat

ion ===

Company Name: BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ

ZIP:07304-3306

Phone: (201) 333-6986

CAGE:FO833

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306 Country:US

Phone:201-333-6986

CAGE:34094

======= Composition/Information on Ingredients ========

Ingred Name:LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA

CAS:64742-89-8

Fraction by Wt: 80-85% ACGIH TLV:300 PPM

Ingre

d Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 3-5% Other REC Limits: 100 PPM OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS =========== Hazards Identification ================= Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: NASAL & RESPIRATORY IRRITATION/CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS/WEAKNESS/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUSNESS/DEATH/BR EATHING DIFFICULTY. EYE: IRRITATION/REDNESS/TEARS /BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION/NAUSEA/VOMITING/DIARRHEA. SKIN: DEFATTING/DERMATITIS/IRRITATION. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: INHALATION: NASAL & RESPIRATORY IRRITATION/CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS/WEAKNESS/FATIGUE/NAUSEA/HEADACHE/UNCONSCIOUSNESS/DEATH/BR **EATHING DIFFICULTY. EYE:** IRRITATION/REDNESS/TEARS /BLURRED VISION. SKIN: IRRITATION/DEFATTING/DERMATITIS. INGESTION: GASTROINTESTINAL IRRITATION/NAUSEA/VOMITING/DIARRHEA. Medical Cond Aggravated by Exposure: DERMATITIS First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT OR STOPS, GIVE ARTIFICIAL RESPIRATION OR OXYGEN. KEEP WARM & QUIE T. I NGESTION: DON'T INDUCE VOMITING. KEEP WARM & QUIET. ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:TCC

Autoignition Temp: Autoignition Temp Text: 480 F

Extinguishing Media: DRY CHEMICAL, CO2, OR FOAM

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APP

Flash Point:72F

Lower Limits: 0.9% Upper Limits: 6%

ARATUS. Unusual Fire/Explosion Hazard:AUTOIGNITION TEMPERATURE: 480F.	
========= Accidental Release Measures ===========	
Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. ABSORB LIQUID ON PAPER/VERMICULITE/FLOOR ABSORBENT/SAND/CLAY/EARTH/ABSORBENT MATERIAL & SHOVEL INTO CONTAINER/TRANSFER TO HOOD. EVACUATE AREA/WEAR PROTECTIVE EQUIPMENT. STOP AT SOURCE/DIKE AREA/PUMP TO SALVAGE TANK.	
============ Handling and Storage ==============	
Handling and Storage Precautions:GROUND OR BOND ALL LARGE METAL CONTAINERS WHEN BEING TRANSFERRED. KEEP AWAY FROM ALL SOURCES OF IGNITION.	F
====== Exposure Controls/Personal Protection ========	
Ventilation:LOCAL EXHAUST OR MECHANICAL VENTILATION Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Supplemental Safety and Health	
========= Physical/Chemical Properties ==========	
Boiling Pt:B.P. Text:240F Melt/Freeze Pt:M.P/F.P Text:	