

PRATTVILLE BUILDERS INC -- CLEAR GLOSS LACQUER -- 8010-00-166-1689

===== Product Identification =====

Product ID: CLEAR GLOSS LACQUER

MSDS Date: 03/11/1991

FSC: 8010

NIIN: 00-166-1689

MSDS Number: BKJGK

=== Responsible Party ===

Company Name: PRATTVILLE BUILDERS INC

Address: 474 E MAIN ST

Box: 2153

City: PRATTVILLE

State: AL

ZIP: 36067

Country: US

Info Phone Num: 205-365-2396/2145/312-455-2662NIGHT

Emergency

Phone Num: 205-365-2396/2145/312-455-2662NIGHT

Preparer's Name: W. A. ELLISON

CAGE: 0EAH4

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box: 6027

City: CLEVELAND

State: OH

ZIP: 44101-1027

Country: US

Phone: 216-566-2902

CAGE: 61196

Company Name: PRATTVILLE BUILDERS INC

Address: 474 E MAIN ST

Box: 2153

City: PRATTVILLE

State: AL

ZIP: 36067

Country: US

Phone: 205-365-2396/2145/312-455-2662NIGHT

CAGE: 0EAH4

===== Composition/Information on Ingredients =====

Ingred Name: TOLUE

NE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE (RESIN)
CAS:9004-70-0
RTECS #:WG2934500
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (SARA 313) (VAPOR PRESSURE 10 MM
HG @ 20C) (LFL: 1.0 UFL: 11.0)
CAS:78-83-1
RTECS #:NS1752000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VM&P NAPHTHA (SOLVENT) (LFL: 1.0 UFL: 6.0)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 15%
Other REC Limits:NONE SPECIFIED
OSHA PEL:300 PPM/400 PPM STEL
ACGIH TLV:300 PPM / 1350 MG/M3

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI

-2-ETHYLHEXYL-PHTHALATE) (SARA
III)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3/10 STEL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 35%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 5.88 LB/GL LESS WATER & NPRS*; 706 G/L LESS WATER;
CALCULAT

ED *NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 40.22 LB/GAL SOLIDS; 4826 G/L SOLIDS; CALCULATED

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INGEST/INHALE/EYE/SKIN: IRRITATION

(GASTROINTESTINAL, NOSE,

THROAT, EYE, SKIN). LUNG ASPIRATION MAY

CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CENTRAL NERVOUS

SYSTEM DEPRESSION. SKIN DEFATTING. OVEREXPOSURE: LIVER DAMAGE.

SOLVENTS ARE ASSOCIATED WITH PERMANENT BRAIN AND NERVOUS SYSTEM

DAMAGE.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE IS LISTED AS A
POTENTIAL CARCINOGEN BY THE NTP.

Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES,
DIZZINESS, NAUSEA, CONFUSION.

Medical Cond Aggravated by Exposur

e:TOLUENE HAS BEEN FOUND TO CAUSE
KIDNEY, LUNG & SPLEEN DAMAGE IN LAB ANIMALS.

===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTROL,
EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH
AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM &
QUIET. GET IMMEDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE
AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE
CONT
AMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER.
PERSISTANT IRRIT GET MED AID.

===== Fire Fighting Measures =====

Flash Point:20.0F,-6.7C
Autoignition Temp:Autoignition Temp Text:572F
Lower Limits:1.0
Upper Limits:13.0
Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR
ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE
FIRES
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, USE TO COOL
CONTAINERS (FOG NO
ZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP &
AUTO- IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT
Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE
TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY
NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE
SOURCES. DIKE, CONTAIN & REMOVE WITH INERT MATERIAL
(SAND, EARTH,
ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE
NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS &
GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE
QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE
INTERNALLY. KEEP FROM CHILDREN. DO NOT REUSE CONTAINERS.
Other Precautions:CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE

RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER.
NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. KEEP
CONTAINERS CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D CHEMICAL CARTRIDGE
RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED.
CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.
EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR
OR W/RIGHT FACTOR.
Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT
VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.
Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE GLOVES.
Eye Protection:SAFETY GLASSES W/SIDESHIELD, FACESHIELD.
Other Protective Equipment:NOT LIKELY TO BE NEEDED.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:180 TO 302F
Melt/Freeze Pt:M.P/F.P Text:-50F,-46C

Decomp Temp:Decomp Text:1832F,1000C
Vapor Pres:40
Vapor Density:> THAN AIR
Spec Gravity:0.9
pH:4-7
Viscosity:< 200 CST
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESS HEAT (>100F) & IGNITION
SOU

RCEs.

Hazardous Decomposition Products: BURNING, INCLUDING HEATED BY WELDING OR CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON DIOXIDE, POSSIBLE NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods: FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS MATERIAL-D001. USE HAZARDOUS WASTE LANDFILL FOR USED ABSORBENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.