

ESGARD INC. -- PL-2 -- 8030-00-244-1295

===== Product Identification =====

Product ID:PL-2

MSDS Date:08/09/1990

FSC:8030

NIIN:00-244-1295

MSDS Number: BKJHJ

=== Responsible Party ===

Company Name:ESGARD INC.

Box:2698

City:LAFAYETTE

State:LA

ZIP:70502

Country:US

Info Phone Num:318-234-7436

Emergency Phone Num:318-234-6327

Preparer's Name:EMILIO BELTRAN

CAGE:KO815

=== Contractor Identification ===

Company Name:ESGARD INC.

Box:2698

City:LAFAYETTE

State:LA

ZIP:705

02

Country:US

Phone:318-234-7436

CAGE:KO815

===== Composition/Information on Ingredients =====

Ingred Name:OIL AS A MIST

Other REC Limits:NONE SPECIFIED

ACGIH TLV:5 MG/M3

Ingred Name:VOC: < 10 G/L (0.1 LBS/GL)

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPOSURE TO VAPORS OR MISTS MAY CAUSE
PULMONARY IRRITATION

, DIZZINESS AND NAUSEA. PROLONGED OR REPEATED
CONTACT MAY CAUSE VARIOUS SKIN DISORDERS SUCH AS DERMATITIS,
FOLLICULITIS OR OIL ACNE.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO UNCONTAMINATED AREA. IF
BREATHING IS IRREGULAR OR STOPPED, PROVIDE OXYGEN OR RESUSCITATION.
SEEK MEDICAL AID. SKIN: FLUSH SKIN THOROUGHLY WITH WATER. REMOVE
CONTAMINATED C LOTHING. EYE: FLUSH EYES THOROUGHLY FOR15 MINUTES
WITH WATER.
SEEK MEDICAL AID. INGEST: DO NOT INDUCE VOMITING. SEEK
IMMEDIATE MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:355F,179C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:PREHEATED MAT'L MAY BURN. DO NOT ENTER
CONFINED AREA W/OUT FULL BUNKER GEAR, AND POSITIVE PRESSURE NIOSH
APPR'D SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER.

===== Accidental Release Measures =====

=====

Spill Release Procedures:CONTAIN THE SOURCE OF THE LEAK IF POSSIBLE.
DIKE AND CONTAIN THE SPILL USING VACUUM OR PUMPS TO REMOVE THE
MATERIAL. SOAK UP ANY EXCESS WITH OIL ABSORBENT MATERIAL. DISPOSE
OF PROPERLY.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT, SPARKS OR OPEN
FLAMES.
Other Precautions:EMPTY CONTAINERS MAY RETAIN HAZARDOUS PROPERTIES. DO
NOT CUT, WELD OR PUNCTURE ON OR NEAR CONTA
INERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED
Ventilation:RECOMMENDED
Protective Gloves:RUBBER/OIL RESISTANT
Eye Protection:CHEMICAL SPLASH GOGGLES
Work Hygienic Practices:MINIMIZE SKIN CONTACT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6
Vapor Density:> AIR
Viscosity:1750 CP
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:1/2

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HEAT, OPEN FLAMES, OXIDIZING MATERIALS

Hazardous Decomposition Products: CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Conditions to Avoid Polymerization: HEAT, OPEN FLAMES, OXIDIZING MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF MATERIAL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.