

PRATT AND LAMBERT INC -- LACQUER SPRAYING CLEAR -- 8010-00-543-7839

=====
Product Identification
=====

Product ID:LACQUER SPRAYING CLEAR

MSDS Date:03/11/1991

FSC:8010

NIIN:00-543-7839

MSDS Number: BKJLM

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL

ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE (RESIN)
CAS:9004-70-0
RTECS #:WG2934500
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ISOB

UTYL ALCOHOL (SOLVENT) (SARA 313) (VAPOR PRESSURE 10 MM
HG @ 20C) (LFL: 1.0 UFL: 11.0)

CAS:78-83-1

RTECS #:NS1752000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE

CAS:142-82-5

R

TECS #:MI7700000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:HEXANE (SOLVENT) (N-HEXANE) (VAPOR PRESSURE 120 MM HG @
20C) (LFL: 1.0 UFL: 8.0)

CAS:110-54-3

RTECS #:MN8420000

Fraction by Wt: < 1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5%

Other

REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 5.45 LB/GL LESS WATER & NPRS*; 654 G/L LESS WATER;
CALCULATED *NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 28.60 LB/GAL SOLIDS; 3432 G/L SOLIDS; CALCULATED
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Route
s of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:IRRITATION (GASTROINTESTINAL, NOSE,
THROAT, EYE, PRIMARY SKIN). LUNG ASPIRATION:CHEMICAL
PNEUMONITIS-CAN BE FATAL. CENTRAL NERVOUS SYSTEM DEPRESSION.
CORNEAL DAMAGE. SKIN ABSORPTION. OVEREXPOSURE: L IVER, KIDNEY,
BLOOD DAMAGE. PERIPHERAL NERVOUS SYS DAMAGE, PERIPHERAL NEUROPATHY,
PERMANENT BRAIN & NERVOUS SYS DAMAGE.

Explanation of C
arcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE, IS LISTED AS
A POTENTIAL CARCINOGEN.
Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES,
DIZZINESS, NAUSEA, CONFUSION.
Medical Cond Aggravated by Exposure:TOLUENE HAS BEEN FOUND TO CAUSE
KIDNEY, LUNG, & SPLEEN DAMAGE IN LAB ANIMALS. METHYL ETHYL KETONE
MAY BE EMBRYOTOXIC, FETOTOXIC & TERATOGENIC.

===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CON
TROL,
EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH
AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM &
QUIET. GET IMM EDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE
AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: IMMEDIATELY
FLUSH WITH WATER WHILE REMOVING CONTAMINATED CLOTHES. CONSULT A
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:-9F,-23C
Autoignition Temp:Autoignition Temp Tex

t:572F

Lower Limits:1.0

Upper Limits:13.0

Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures:USE SCBA. WATER MAY BE INEFFECTIVE, USE TO COOL CNTNRS(FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP&AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE GEAR. SPECTATORS AWAY. ELIMINATE IGNITE SOURCES. DIKE, CONTAIN&REMOVE W/INERT MATERIAL (EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS,GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. DO NOT REUSE CONTAINERS FOR ANY PURPOSE.

Other Precautions:CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. KEEP CONTAINERS CLOSED WHEN NOT IN USE. CLOSE CNTNRS AFTER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D ORGANIC CARTRIDGE RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR W/RIGHT FACTOR.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.

Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE

GLOVES.

Eye Protection:SAFETY GLASSES, CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:EYE WASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:156 TO 302F

Melt/Freeze Pt:M.P/F.P Text:-50F,-46C

Decomp Temp:Decomp Text:1832F,1000C

Vapor Pres:120

Vapor Density:> THAN AIR

Spec Gravity:0.9

pH:4-7

Viscosity:15-35 SEC. F4

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility i

n Water:SLIGHT

Appearance and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:80

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESS HEAT (>100F) & IGNITION SOURCES.

Hazardous Decomposition Products:BURNING, INCLUDING HEATED BY WELDING/CUTTING PRODUCES SMOKE, CARBON MONOXIDE & CARBON DIOXIDE, POSSIBLE NITROGEN OXIDES.

=

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS MATERIAL-D001. USE HAZARDOUS WASTE LANDFILL FOR USED ABSORBENTS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The U

nited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.