

JET-LUBE INC. -- KOPR-KOTE (R) LEAD-FREE -- 8030-00-286-5453

===== Product Identification =====

Product ID:KOPR-KOTE (R) LEAD-FREE

MSDS Date:07/10/1991

FSC:8030

NIIN:00-286-5453

MSDS Number: BKKDH

=== Responsible Party ===

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Info Phone Num:713-674-7617

Emergency Phone Num:713-674-7617

Preparer's Name:D A OLDIGES

CAGE:JO923

=== Contractor Identification ===

Company Name:JET-LUBE INC

Address:4849 HOMESTEAD RD

Box:21258

City:HOUSTON

State:TX

ZIP:77026

Country:US

CAGE:0A307

Company Name:JET-LUBE INC.

Address:4849 HOMESTEAD ROAD

Box:21258

City:HOUSTON

State:TX

ZIP:77226

Country:US

Phone:713-674-7617

CAGE:JO923

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL

CAS:64741-96-4

RTECS #:PY8040000

Fraction by Wt: 70% MAX

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

Ingred Name:COPPER POWDER (SAR

A III)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 12% MAX
Other REC Limits:NONE SPECIFIED
ACGIH TLV:1 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:REPEATED SKIN CONTACT FOR PERSONS
HYPERSENSITIVE TO PETROLEUM PRODUCTS CAN CAUSE REDNESS AND
IRRITATION OF SKIN.
Effects of Overexposure:REDNESS AND IRRITATION OF SKIN.

===== First Aid Measures =====

First Aid:INHALATION: CLEAR AIR PASSAGES, CALL PHYSICIAN. INGESTION: IF
INGESTED, CALL PHYSICIAN. EYES: WASH WITH COPIOUS QUANTITIES OF
WATER. SKIN: REMOVE BY WIPING, OR WATERLESS HAND CLEANER, FOLLOWED
BY WASH ING.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:465F,241C
Autoignition Temp:Autoignition Temp Text:500F
Extinguishing Media:USE FOAM, DRY CHEMICAL, WATER
SPRAY (FOG), CARBON
DIOXIDE OR VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.
Fire Fighting Procedures:USE SUPPLIED-AIR BREATHING EQUIPMENT FOR
ENCLOSED OR CONFINED SPACES.
Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS, WIPE UP WITH RAGS, PICK-UP
RESIDUE WITH DIATOMACEOUS EARTH TO AVOID WALKING HAZARD.

===== Handling and Storage =====

Handling and St

Storage Precautions:NORMAL PRECAUTIONS AS WITH ANY
PETROLEUM PRODUCT.

===== Exposure Controls/Personal Protection =====

Other Protective Equipment:PERSONS WITH HYPERSENSITIVE SKIN SHOULD USE
GLOVES.

Work Hygienic Practices:WASH HANDS BEFORE EATING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:624F,329C

Vapor Pres:5

Spec Gravity:1.14 (WATER=1)

Evaporation Rate & Reference: