

FLYING J INC -- #2 DIESEL -- 9140-00-286-5297

===== Product Identification =====

Product ID:#2 DIESEL
MSDS Date:02/13/1992
FSC:9140
NIIN:00-286-5297
MSDS Number: BKNVL
=== Responsible Party ===
Company Name:FLYING J INC
Address:48 W 990 S
Box:678
City:BRIGHAM CITY
State:UT
ZIP:84302-3121
Country:US
Info Phone Num:801-298-7733
Emergency Phone Num:800-424-9300
CAGE:3R475
=== Contractor Identification
n ===
Company Name:FLYING J INC
Address:48 W 990 S
Box:678
City:BRIGHAM CITY
State:UT
ZIP:84302-3121
Country:US
Phone:801-298-7733
CAGE:3R475

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT
CAS:8008-20-6
RTECS #:OA5500000
Other REC Limits:100 MG/M3 8 HR TWA

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 10,000 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-EYE:NO SIGNIFICANT HAZARDS.SKIN:
REPEATED/PROLONGED CONTACT CAN CAUSE IRRITATION.INHALATION:NONE
EXPECTED UNDER NORMAL CONDITIONS OF USE.INHALATION OF MIST/HIGH
CONCENTRATION OF VAPORS CAN PRODU CE DIZZINESS,HEADACHE & IRRITATES
EYE,NOSE & THROAT. INGESTION:HARMFUL IF ASPIRATED INTO
LUNG.CHRONIC-NOT GIVEN.

Explanation of Carcinogenicity:EXPOSURE TO DIESEL EXHAUST SHOULD BE
MINIMIZE

D TO REDUCE THE POTENTIAL CANCER RISK.

Effects of Overexposure:THIS MATERIAL IS AN ASPIRATION HAZARD,A SKIN
IRRITANT AND MAY BE A SKIN CANCER HAZARD BASED ON TESTS WITH
LABORATORY ANIMALS. PRIMARY EXPOSURE ROUTE IS SKIN CONTACT.
INHALATION IF VAPORS OR MISTS ARE GENERATED.

Medical Cond Aggravated by Exposure:NOT GIVEN

===== First Aid Measures =====

First Aid:GET MEDICAL CARE. INHALATION: REMOVE TO FRESH AIR.
RESUSCITATE IF NEEDED. EYE/SKIN
: FLUSH WITH WATER FOR SEVERAL
MINUTES. WASH SKIN WITH SOAP & WATER. INGESTION: CALL A PHYSICIAN
IMMEDIATELY. DO NOT I NDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:150F,66C

Lower Limits:0.4%

Upper Limits:6%

Extinguishing Media:WATER FOG, CO2, FOAM, OR DRY CHEMICAL. DO NOT USE
SPRAY OR A DIRECT STREAM OF WATER.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.

COOL FIRE EXPOSED

CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:FOR FIRE INVOLVING THIS MATERIAL, DO NOT
ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE
EQUIPMENT. HAVE ADEQUATE VENTILATION.

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP SMALL SPILLS/RESIDUE WITH INERT
ABSORBENT. FOR LARGE SPILLS, WEAR PROTECTIVE EQUIPMENT. REMOVE ALL
IGNITION SOURCES. DIKE & CONTAIN SPILLS. DON'T ALLOW S

PILLS TO
ENTER SEWERS,STREAMS ETC. PICK UP SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL, DRY
WELL-VENTILATED AREA IN CLOSED CONTAINER AWAY FROM HEAT,IGNITION
SOURCES & OXIDIZERS.

Other Precautions:COMBUSTIBLE LIQUID. USE WITH ADEQUATE VENTILATION.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING. LAUNDRY CONTAMINATED
CLOTHING BEFORE REUSE. TO PREVENT RISK OF SKIN CANCER, PROTECT YOUR
SKIN WITH
GLOVES AND IMPERVIOUS CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN SITUATION WHERE VAPOR CONCENTRATIONS MAY
EXCEED THE RECOMMENDED EXPOSURE LIMITS, A NIOSH-APPROVED ORGANIC
VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED
SUPPLIED-AIR RESPIRATOR FOR EMERGENCIES.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF
LOCAL EXHAUST TO KEEP VAPOR BELOW RECOMMENDED EXPOSURE LIMITS

Protecti

ve Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR
PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

H

CC:V4

Boiling Pt:B.P. Text:330F,166C

Spec Gravity:0.8

Viscosity:2-4 CST @100F

Solubility in Water:NEGLIGIBLE (