

BAKER SEALANTS AND COATINGS CO -- PAINT FOR CONCRETE AND MASONRY
8010-00-054-9322

===== Product Identification =====

Product ID:PAINT FOR CONCRETE AND MASONRY

MSDS Date:11/05/1990

FSC:8010

NIIN:00-054-9322

MSDS Number: BKPFP

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6986/800-356-3129(CHEMTREC)

Pr

Preparer's Name:CHARLES FRIEDMAN

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

===== Composition/Information on Ingredients =====

Ingredient Name:PETROLEUM SOLVENT

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 20-25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM TLV

Ingredient Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS525000

0
Fraction by Wt: 7-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 0.1-0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:COBALT
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 105F,>41C
Autoignition Temp:Autoignition Temp T
ext:480 F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON
DIOXIDE.
Fire Fighting Procedures:DO NOT USE DIRECT WATER STREAM. PRODUCT WILL
FLOAT AND CAN BE REIGNITED ON WATER SURFACE. KEEP UNPROTECTED
PERSONNEL FROM AREA. WEAR PROPER PROTECTIVE EQUIP.
Unusual Fire/Explosion Hazard:COOL CNTNRS EXPOSED TO INTENSE HEAT
W/WATER/ POSS CNTNR RUPTURE. COOL CONTAINER AREAS EXPOSED TO DIRECT
FLAME W/LARGE AMT WATER TO PREVENT STRUCTURE W
EAKENING.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITE SOURCES. WEAR APPROP PROTECT
EQUIP. SHUT OFF LEAK SOURCE IF SAFE. DIKE & CONTAIN. REMOVE
W/VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP
W/ABSORB. PLACE IN NONLEAK CNTNRS FOR PROPER DISPOSAL. SEAL
TIGHTLY.FLUSH AREA W/WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQUID & VAPOR AWAY

FROM IGNITE
SOURCES. HOT SURFACES MAY IGNITE EVEN LIQUID W/O SPARKS OR FLAME.
Other Precautions:VAPORS MAY ACCUMULATE & TRAVEL TO IGNITION SOURCES
DISTANT FROM HANDLING SITE; FLASH-FIRE CAN RESULT. KEEP CONTAINERS
CLOSED WHEN NOT IN USE. USE W/ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL
EXPOSURE LIMITS, USE A NIOSH-APPROVED RESPIRATOR AS REQUIRED TO
PREVENT OVER
EXPOSURE. USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR
OR AN AIR- PURIFYING RES PIRATOR FOR ORGANIC VAPORS.
Ventilation:USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL
VAPOR CONCENTRATIONS WITHIN SUGGESTED PEL/TLV LIMITATIONS.
Protective Gloves:CHEMICAL-RESISTANT GLOVES.
Eye Protection:SAFETY GLASSES OR GOGGLES ARE APPROP.
Other Protective Equipment:OTHER CLOTHING AS REQUIRED TO MINIMIZE.
Supplemental Safety and Health
CAUTION!!! COMBUSTIBLE!!! FEDERAL REGULATION REPORTABLE QUANT
ITY: THIS
PRODUCT IS CLASSIFIED AS AN OIL UNDER SECTION 311. SPILLS INTO OR
LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED T O
THE NATIONAL RESPONSE CENTER, 800-424-8802.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315 TO 395F
Melt/Freeze Pt:M.P/F.P Text:NIF
Decomp Temp:Decomp Text:NIF
Vapor Pres:3.0 MM HG
Vapor Density:3.9
Spec Gravity:1.25
pH:6.5
Viscosity:67-82 KU
Evaporation Rate & Reference:2 (BUAC = 1)
So
lubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE, ALIPHATIC ODOR
Percent Volatiles by Volume:102

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID HEAT, FLAME, CONTACT W/STRONG OXIDIZING AGENTS(E.G. LIQUID
CHLORINE, CONC OXYGEN, SODIUM OR CALCIUM HYPOCHLORITE).
Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED
ORGANIC COMPOUNDS DURING COMBUSTION.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF AS PER LOCAL, STATE AND FEDERAL REGULATIONS. SEAL CONTAINERS, LABEL PROPERLY & DISPATCH TO APPROVED WASTE DISPOSAL FACILITY-D001. IF THIS PRODUCT BECOMES A WASTE MATERIAL, IT WOULD BE IGNIT ABLE HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.