

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET

MSDS Date:07/09/1986

FSC:4730

NIIN:00-216-6151

MSDS Number: BKPGN === Responsible Party ===

Company Name: FLEXITALLIC GASKET CO INC

Address:6915 LAPORTE ROAD

Box:760

City:DEER PARK

State:TX ZIP:77536 Country:US

Info Phone Num:713-479-3491

Emergency Phone Num:713-479-3491

CAGE:58156 === Contractor Identification ===

Company Name: ALPHA MFG CO (AUTOMATION DEVICES INC)

Address:7610 FM 3180 Box:City:BAYTOWN

State:TX ZIP:77520 Country:US

Phone:713-383-3403

CAGE:1N196

Company Name: FLEXITALLIC GASKET CO INC.

Address:6915 LAPORTE RD

Box:760

City:DEER PARK

State:TX ZIP:77536 Country:US

Phone:713-479-3491

CAGE:58156

====== Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:Cl6478500

Other REC Limits: NONE SPECIFIED

OSHA PEL:0.2 FIB

Ingred Name: NONHAZARDOUS INGREDIENTS Other REC Limits: NONE SPECIFIED ========== Hazards Identification =============== LD50 LC50 Mixture: NOT SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Health Hazards Acute and Chronic:BREATHING OF ASBESTOS FIBERS IN SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER. Explanation of C arcinogenicity: ASBESTOS FIBERS HAVE BEEN ASSOCIATED WITH DEVELOPMENT OF CANCER IN HUMANS. Effects of Overexposure: IRREVERSIBLE LUNG DISEASE AND CANCER. Medical Cond Aggravated by Exposure: PRE-EXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE. First Aid: IN CASE OF EYE CONTACT, FLUSH WITH WATER FOR 15 MINUTES. CONTACT A PHYSICIAN IF IRRITATION OCCURS. ====== Fire Fighting Measures ===== Flash Point: NONFLAMMABLE Lower Limits: NONE **Upper Limits:NONE** Extinguishing Media: NONFLAMMABLE. USE MEDIA SUITABLE FOR SURROUNDING Fire Fighting Procedures: NONFLAMMABLE. USE PROCEDURES SUITABLE FOR SURROUNDING FIRE. Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

Spill Release Procedures: VACUUM FINES AND DUST CAREFULLY AVOIDING

DUSTING. IF SWEEPING IS USED, CONTROL DUST BY WETTI

ERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

NG AREA AND USE APPROPRIATE RESPIRATORY PROTECTION. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:PRODUCT IS A SPIRAL WOUND GASKET. NO SPECIAL HANDLING OR STORAGE REQUIRED. Other Precautions:SEE OTHER REGULATIONS FOR ASBESTOS HANDLING IN CFR TITLE 29, PART 1910, SUBPART 2, PAR 1910.1001.
======= Exposure Controls/Personal Protection =========
Respiratory Protectio n:USE MSA/OSHA RESPIRATOR IF DESIRED. Ventilation:CONSULT LOCALLY APPLICABLE REGULATIONS FOR EMISSION. Protective Gloves:NONE SPECIFIED BY MANUFACTURER. Eye Protection:NONE SPECIFIED BY MANUFACTURER. Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:KEEP WORK AREA CLEAN OF ASBESTOS DUST. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER.
========= Physical/Chemical Properties ===========
HCC:N1 Boiling Pt:B.P. Text:NONE Vapor Pres: NONE Vapor Density:NONE Spec Gravity:2.5 Evaporation Rate & Description Reference:NIL Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT BLUE; NO ODOR Percent Volatiles by Volume:0 %
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.
======== Disposal Considerations

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS FOR DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.