

ELE CORP., THE -- HT-2220 PAINT REMOVER -- 6850-00-281-3042

===== Product Identification =====

Product ID:HT-2220 PAINT REMOVER

MSDS Date:10/05/1988

FSC:6850

NIIN:00-281-3042

MSDS Number: BKSMN

=== Responsible Party ===

Company Name:ELE CORP., THE

Address:7847 WEST 4TH STREET

Box:34837

City:LYONS

State:IL

ZIP:60534

Country:US

Info Phone Num:312-442-9100

Emergency Phone Num:312-442-9100

Preparer's Name:PAT E. SMITH

CAGE:0ET57

=== Contractor Identification ===

C

Company Name:ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837

Country:US

Phone:800-531-1088/ 210-653-2060

CAGE:55208

Company Name:ELE CORP., THE

Address:7847 WEST 4TH STREET

Box:34837

City:LYONS

State:IL

ZIP:60534

Country:US

Phone:312-442-9100

CAGE:0ET57

===== Composition/Information on Ingredients =====

Ingred Name:ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA P

EL:3 PPM/6 STEL
ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION:ACUTE-SLIGHT, VAPOR HAZARD
SKIN CONTACT:ACUTE-LOW. HAZARD. SKIN ABSORPTION: ACUTE-LOW,
CHRONIC-NONE. EYE CONTACT: LOW
HAZARD.
Effects of Overexposure:INHALATION:MAY CAUSE SKIN IRRITATION OR
DIFFICULTY IN BREATHING WITH SENSITIVE INDIVIDUALS. SKIN
CONTACT:MAY CAUSE SKIN IRRITATION. NO CHRONIC EFFECTS EXPECTED.
SKIN ABSORPTION:NO EVIDENCE OF SKIN ABSORPTION HAZARD. EYE
CONTACT:IRRITATION TO EYES.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP &
WATER. INHALATION:REMOVE TO FRESH AIR. INGESTION:INDUCE V
OMITING,
CONTACT PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:CO2 & FOAM.
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS REQUIRED.
AVOID SKIN CONTACT.
Unusual Fire/Explosion Hazard:WILL CREATE NITROGEN OXIDES DURING
COMBUSTION. (PH:@ 10% DILUTION 10)

===== Accidental Release Measures =====

Spill Release Procedures:RINSE

WITH WATER

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS IF LIMITS
EXCEEDED

Ventilation:100 FT/MIN AIR FLOW.

Protective Gloves:RUBBER

Eye Protection:FACE SHIELD

Other Protective Equipment:RUBBER APRONS & BOOTS

Supplemental Safety and Health

USED AT 180F, AVOID BURNS. AVOID SKIN CONTACT.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:B.P. Text:>240F,>116C

Melt/Freeze Pt:

M.P/F.P Text: