

FINA OIL AND CHEMICAL CO -- DIESEL/FURNACE OIL (#2 OIL) -- 9140-00-286-5296

===== Product Identification =====

Product ID:DIESEL/FURNACE OIL (#2 OIL)
MSDS Date:04/14/1989
FSC:9140
NIIN:00-286-5296
MSDS Number: BKSPV
=== Responsible Party ===
Company Name:FINA OIL AND CHEMICAL CO
Address:8350 N CENTRAL EXPY
Box:2159
City:DALLAS
State:TX
ZIP:75221-9986
Country:US
Info Phone Num:409-962-4421
Emergenc
y Phone Num:409-962-4421, CHEMTREC 800-424-9300
CAGE:0B1N6
=== Contractor Identification ===
Company Name:FINA OIL AND CHEMICAL CO
Address:8350 N CENTRAL EXPY
Box:City:DALLAS
State:TX
ZIP:75206
Country:US
Phone:214-750-2400
CAGE:0B1N6

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM MID-DISTILLATE
CAS:68476-34-6
Other REC Limits:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ing

estion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INGESTION:HARMFUL OR FATAL.

ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONIA AND CAN BE FATAL. INHALATION OF MIST MAY CAUAE IRRITATION OF NOSE & THROAT.

EYE: IRRITATION. SKIN: IRRITATION. CHR ONIC-PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION, DERMATITIS.

Effects of Overexposure:INHALATION MAY CAUSE IRRITATION OF NOSE, THROAT AND DIZZINESS. PROLONGED OR REPEATED SKI

N CONTACT MAY CAUSE SKIN

IRRITATION. EYE CONTACT MAY CAUSE EYE

IRRITATION.INGESTION:VOMITING, WEEKNESS, COMA, CO NVUSIONS.

Medical Cond Aggravated by Exposure:PERSONS WITH SKIN & PULMONARY

DISORDERS SHOULD AVOID PROLONGED CONTACT WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO

FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:130F,54C

Autoignition Temp:Autoignition Temp Text:450F

Extinguishing Media:USE HALON, CARBON DIOXIDE, FOA M, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT, OR ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MAT

ERIAL. STORE IN APPROPRIATE

CONTAINER FOR DISPOSAL. KEEP PRODUCT OUT OF SEWERS AND WATERCOURSES
BY DIKING OR IMPOUNDING. MINIM IZE SKIN CONTACT AND BREATHING
VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE NEAR OPEN FLAME OR OTHER
SOURCES OF IGNITION,AND STRONG OXIDANTS. KEEP CONTAINERS CLOSED.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE. DO NOT PRESSURIZE,
CUT, WELD OR EXPOSE TO HEAT, FLAME, S
TATIC ELECTRICITY, OR OTHER
SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SUPPLIED-AIR RESPIRATORY PROTECTION IN
CONFINED OR ENCLOSED SPACES, IF NEEDED.

Ventilation:SUFFICIENT TO MAINTAIN ATMOSPHERE BELOW TLV LIMIT.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. CHEMICA
LLY

RESISTANT BOOTS AND APRONS RECOMMENDED.

Work Hygienic Practices:DO NOT TAKE INTERNALLY. AVOID SKIN/EYE CONTACT.
WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

WASH OR TAKE SHOWER IF GENERAL CONTACT OCCURS. REMOVE OIL-SOAKED
CLOTHING AND LAUNDER BEFORE REUSE. DISCARD CONTAMINATED LEATHER
GLOVES AND SHOES.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:320F,160C

Vapor

Pres:1.6 MMHG

Vapor Density:8.0

Spec Gravity:0.87

Evaporation Rate & Reference: