PRATT AND LAMBERT INC -- LAC ACR ORANGE 12197 ID794297 -- 8010-00-935-7065

Product ID:LAC ACR ORANGE 12197 ID794297

MSDS Date:12/06/1990

FSC:8010

NIIN:00-935-7065

MSDS Number: BKSVD === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Box:2153 City:WICHITA State:KS ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W. A. ELLISON

CAGE:61196 === Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000 Fraction by Wt: 20%

Other REC Limits: NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA927500

0

Fraction by Wt: 10%

Other REC Limits: NONE SPECIFIED

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

AC

GIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)

CAS:85-68-7

RTECS #:TH9990000 Fraction by Wt: < 5%

Other REC Limits: NONE SPECIFIED

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:LEAD CHROMATE (SARA 313)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt:

15%

Other REC Limits:NONE SPECIFIED OSHA PEL:.05MG/M3/.1MG/M3CEIL

ACGIH TLV:0.0500 MG/M3

Ingred Name: LEAD SULFATE (SARA III)

CAS:7446-14-2

RTECS #:OG4375000 Fraction by Wt: 5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:SEE 1910.1025

ACGIH TLV:0.15 MG PB/M3; 9192

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name: MOLYBDENUM-SOLUBLE COMPOUNDS

CAS:7439-98-7

RTECS #:OA4680000 Fraction by Wt: < 1%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingred Name:METHYL

ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 5%

Other REC Limits: NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: VOC: 5.10 LB/GL LESS WATER & NPRS*; 612 G/L LESS WATER; CALCULATED *NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS

RTECS #:9999999VO

Other REC Limits: NONE SPECIFIED

Ingred Name: VOC: 17.81 LB/GAL SOLIDS; 2137 G/L SOLIDS; CALCULATED

RTECS #:9999999VO

Other REC

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES | IARC:YES | OSHA:YES

Health Hazards Acute and Chronic:IRRITATION (GASTROINTEST, NOSE, THROAT, EYE, SKIN). ASPIRATION TO LUNGS: CHEMICAL PNEUMONITIS-CAN BE FATAL. CENTRAL NERVOUS SYS DEPRESSION. SKIN: DEFATTING. OVEREXPOS: LUNG CANCER. LIVER DAMAGE. SEVER E DAMAGE: BLOOD FORMING, NERVOUS, URINARY

- & REPRODUCTIVE SYS. PERIPHERAL NEUROPATHY. PERM BRAIN & NERVOUS SYS DAMAGE.
- Explanation of Carcinogenicity:CHROMIUM & CERTAIN CHROMIUM COMPOUNDS, LEAD CHROMATE, DI(2-ETHYLHEXYL)PHTHALATE, ARE LISTED AS CARCINOGENS.
- Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES, DIZZINESS, NAUSEA, CONFUSION. CHRONIC OVEREXPOSURE: NO APPETITE, METALLIC TASTE IN MOUTH, ANXIETY, CONSTIPATION, NAUSEA, WEAKNESS, INSOMNIA, HEADACHE, MUSCL E/JOINT PAIN, FINE TREMORS, NUMBNESS
- DIZZINESS, HYPERACTIVITY & COLIC. METAL FUME FEVER:FLU-LIKE, FEVER, CHILLS, COUGH.
- Medical Cond Aggravated by Exposure:PRE-EXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD. OVEREXPOS TO SOLVENTS ARE ASSOCIATED W/PERMANENT BRAIN AND NERVE SYS DAMAGE. LAB STUDIES W/RATS INDICATE MIBK DAMAGE THE KIDNEYS.

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTROL, EMERGENCY ROOM OR PH

YSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH
AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM &
QUIET. GET IMM EDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE
AMOUNTS OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE
CONTAMINATED CLOTHES WASH AFFECTED AREA WITH SOAP & WATER.
PERSISTANT IRRIT/MEDICAL AID.

============= Fire Fighting Measures ========================

Flash Point:1F,-17C Lower Limits:.3 Upper Limits:13.0

Extinguishing Media: USE NF

PA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures: USE SCBA. WATER MAY BE INEFFECTIVE, USE TO COOL CNTNRS(FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP&AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:EMERGENCY CONDITIONS:OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT. GET MEDICAL AID. VAPORS MAY CAU SE FLASH FIRE.

 Accidental Release Measures	
 Accidental Nelease Measures	

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE IGNITE SOURCES. DIKE AND CONTAIN. REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS AND GROUNDWATER.

========== Handling and Storage ============

Handling and Storage Precautions: DO NOT STORE ABOVE 1 00F. LARGE

QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CONTAINERS CLOSED AFTER USE.

Other Precautions:DO NOT REUSE CONTAINERS FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A P RESSURE VESSEL.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D CHEMICAL CARTRIDGE

RESPIRATOR. SPRAYING:MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. EXCEEDED TLV AREA: NIOSH/MSHA A PPR'D RESPIRATOR W/RIGHT PROTECT FACTOR.

Ventilation: GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.

Protective Gloves: REPEAT/PROLONG USE: IMPERMEABLE GLOVES.

Eye Protection: WEAR SAFETY SPECTACLES

Other Protective Equipment: AS REQUIRED TO PREVENT SK

IN CONTACT, SEE
OSHA STANDARDS FOR LEAD.
Work Hygionic Practices: DO NOT RPEATHE SANDING DUST, WASHIELD

Work Hygienic Practices: DO NOT BREATHE SANDING DUST. WASH HANDS AND FACE BEFORE EATING OR DRINKING.

Supplemental Safety and Health

HAZARDOUS/TOXIC, POSSIBLE HAZARDOUS/TOXIC INGREDIENTS/WASTE. REFER TO OSHA 29CFR1910 FOR SAFETY/PROTECTIVE REQUIREMENTS. WELDING, BRAZING OR TORCH CUTTING MATERIALS COATED WITH THIS PRODUCT MAY PRODUC E METAL OXIDES.

======== Physical/Chemical Properties ===========

Boiling Pt:B.P. Text :133 TO 312F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Density:> AIR Spec Gravity:1.1

pH:NA

Evaporation Rate & Evaporation R

Solubility in Water:NA

Appearance and Odor:PAINT Percent Volatiles by Volume:71

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID HIGH TEMP->100F & IGNITION SOURCES.

Hazardous Decomposition Products:BURNING (INCL WELD/CU

T) PRODUCES

SMOKE, CARBON MONOXIDE, CARBON DIOXIDE. OXIDES: CHROMIUM AND LEAD MAY BE GENERATED.

======= Disposal Considerations ============

Waste Disposal Methods:FOLLOW FEDERAL, STATE & LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS/TOXIC MATERIALS-D001/D008. USE HA ZARDOUS WASTE LANDFILL FOR USED ABSORBENTS.

Disclaimer (provided with this informatio

n by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.