

PRATT AND LAMBERT INC -- LAC ACR BLUE 15044 ID794504 -- 8010-00-935-7072

=====
Product Identification
=====

Product ID:LAC ACR BLUE 15044 ID794504

MSDS Date:12/06/1990

FSC:8010

NIIN:00-935-7072

MSDS Number: BKSVG

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METH

YL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL BENZYL PHTHALATE (SARA III)
CAS:85-68-7
RTECS #:TH9990000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL

KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 5.15 LB/GL LESS WATER & NPRS*; 618 G/L LESS WATER;

CALCULATED *NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 18.26 LB/GAL SOLIDS; 2191 G/L SOLIDS; CALCULATED

RTECS #:9999999VO

Other REC Limi

ts:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST/INHALE/EYE/SKIN: IRRITATION

(GASTROINTESTINAL, NOSE, THROAT, EYE, SKIN). LUNG ASPIRATION MAY

CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CENTRAL NERVOUS

SYSTEM DEPRESSION. CORNEAL DAMAGE. S KIN ABSORPTION. OVEREXPOSURE:

LIVER DAMAGE. PERIPHE

RAL NEUROPATHY, PERMANENT BRAIN AND NERVOUS

SYSTEM DAMAGE.

Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES,

DIZZINESS, NAUSEA, CONFUSION.

Medical Cond Aggravated by Exposure:TOLUENE MAY CAUSE KIDNEY, LUNG &

SPLEEN DAMAGE IN LAB ANIMALS. LAB STUDIES W/RATS SHOW EVIDENCE

METHYL ETHYL KETONE MAY BE EMBRYOTOXIC, FETOTOXIC & TERATOGENIC.

MIBK MAY DAMAGE THE KIDNEYS IN LAB RATS

=====
===== First Aid Measures =====

First Aid:INGES

T: DO NOT INDUCE VOMITING. CALL POISON CONTROL, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM & QUIET. GET IMMEDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER. PERSISTANT IRRIT GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Po

int:1F,-17C

Lower Limits:.3

Upper Limits:13.0

Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures:USE SCBA. WATER MAY BE INEFFECTIVE, USE TO COOL CNTNRS(FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP&AUTO-IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE

A HEALTH HAZARD. SYMPTOMS MAY

NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES. DIKE, CONTAIN & REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS & GROUNDWATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CONTAINERS CLOSED AFTER USE.

Other Precautions:DO NOT REUSE CONTAINERS FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL.

=====
===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED.
CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.
EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR W/RIGHT FACTOR.
Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.
Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE GLOVES.
Eye Protection:SAFETY GLASSES W/SIDESHIELD, FACESHIELD.
Other Protective Equipment:NOT LIKELY TO BE NEEDED.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:133 TO 314F
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Density:> AIR
Spec Gravity:1.0
pH:NA
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:NA
Appearance and Odor:PAINT
Percent Volatiles by Volume:71

===== Stability and Reactivity Data =====

==

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID HIGH TEMP->100F & IGNITION SOURCES.
Hazardous Decomposition Products:BURNING,INCLUDING HEATED BY WELDING OR CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE

CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS MATERIAL-D001. USE HAZARDOUS WASTE LANDFILL FOR USED ABSORBENT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.