

EVERSEAL MFG CO INC -- WHITE PRIMER -- 8010-00-282-9414

===== Product Identification =====

Product ID:WHITE PRIMER

MSDS Date:06/17/1988

FSC:8010

NIIN:00-282-9414

MSDS Number: BKZYD

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657

Country:US

Info Phone Num:201-943-4986

Emergency Phone Num:201-943-4986

CAGE:72988

=== Contractor Ident

ification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 24%

Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 17%

Other REC Limits:AS DUST 15 MG/M3

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (M

ARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 10%

Other REC Limits:AS DUST 10 MG/M3

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 24%

Other REC Limits:AS DUST 2 MG/M3

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 5 MM HG)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 23%

Other REC Limits:5G/KG (ORAL);120 PPM

Ingred Name:

ADDITIVE

Fraction by Wt: 2%

Other REC Limits:NONE SPECIFIED

==== Hazards Identification =====

LD50 LC50 Mixture:5 G/KG ORAL

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA,
POSSIBLE UNCONSCIOUSNESS. IRRITATION TO SKIN AND EYES.

==== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION
IF NECESSARY.

EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP & WATER.
CONSULT PHYSICIAN.

==== Fire Fighting Measures =====

Flash Point:105F,41C

Lower Limits:1

Extinguishing Media:FOAM, CO2, DRY CHEMICAL.

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING
APPARATUS.

==== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE

ADEQUATE

VENTILATION. ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE SPARK- PROOF SCOOP FOR LARGER SPILLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION SOURCES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK.

Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED.

Protective Gloves:IMPERVIOUS

Eye

Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:323 TO 390F

Vapor Density:> AIR

Spec Gravity:11.8 LBS/GL

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:42

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

H

azardous Decomposition Products:CARBON MONOXIDE AND/OR CARBON DIOXIDE ON COMBUSTION.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS PER LOCAL & FEDERAL REGULATIONS FOR HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this

information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.